



INITIA

GEOTECHNICAL SPECIALISTS

AMBURY PROPERTIES

PROPOSED PLAN CHANGE
231 TAHUNA ROAD, OHINEWAI

GEOTECHNICAL ASSESSMENT REPORT

INITIA REF P-000529 REV A

OCTOBER 2019

Your Report Summary

The summary below outlines the principal geotechnical considerations for the site located at 231 Tahuna Road, Ohinewai. It is important that reference is made to the relevant sections in the main body of the report for further detail.

Report Ref	Geotechnical Consideration	Summary Advice/Recommendations
3.0	Geology and Groundwater Conditions	The site is generally underlain by a surficial layer (3 to 13 m thick) of alluvial soils comprising recently deposited sands (Taupo Pumice Alluvium) and very soft clays/silts and peat (Rotokawau Formation). Older alluvial soils (interbedded sands, silts, clays and peat) of the Karapiro, Puketoka and Whangamarino Formations underlie these surficial soils. The basement rock (interbedded claystone, sandstone, siltstone and coal measures) known as the Te Kuiti Formation occurs at a depth of approximately 100 m below ground level. Groundwater is present from near surface levels (0.5 to 1.0 m depth)
3.2	Site Stratigraphy and Zoning	Low lying areas of the site (below RL 7.5 m) are typically mantled by between 5 and 10 m of highly compressible soils (Rotokawau Formation). Areas of the site with higher ground surface elevations (RL 9.0 m or higher) are directly underlain by more competent soils (Karapiro & Puketoka Formation). Refer Figure 529-002 in Appendix A.
4.4.3 and 4.4.4	Liquefaction	The surface soils (Taupo Pumice Alluvium) are predominantly sandy and saturated. These soils, together with the deeper Karapiro/Puketoka Formation sands, are susceptible to liquefaction under an ultimate limit state (ULS) earthquake event. Without mitigation measures, liquefaction of near surface soils could cause failure of shallow foundations which presents a 'life-safety' risk for future buildings. Pavements, buried services (pipes, manholes and tanks) can also be badly damaged. Mitigation of liquefaction effects will need to be addressed for detailed design of buildings and civil infrastructure. Refer to Figure 529-003 in Appendix A.
4.5.2	Settlement	The soils at this site are considered to be highly compressible and could be expected to settle by between 100 mm and 2,000 mm under typical building surcharge pressures of 45 kPa or greater without improvement measures. Low lying areas of the site that are underlain by greater thicknesses of the Rotokawau Formation soils (very soft silts/clays and peat) are at greater risk of settlement. Where, possible future development in these areas should be avoided or minimised. Refer to Figure 529-004 in Appendix A
4.7.2	Ground Improvements	Ground improvements will be required to support future development of buildings, roads, yard areas, and the rail siding across the site. There are a wide range of ground improvement options available, varying between deep pile foundations to preloading. Refer to Table 4-4
5	Further work	Additional geotechnical investigations, analysis and design will be required to confirm and develop ground improvement options and to provide detailed geotechnical advice for design of the site earthworks, civil infrastructure and individual buildings.



Contents

1. Introduction.....	5
1.1 Objective.....	5
1.2 Background and Proposed Development.....	5
2. Project Site	6
2.1 Location.....	6
2.2 Description	6
2.3 Published Geology.....	6
3. Geotechnical Investigations and Subsurface Conditions.....	8
3.1 General	8
3.2 Site Stratigraphy	8
3.3 Test Results	11
3.4 Groundwater	13
4. Geotechnical Considerations for Development.....	14
4.1 Overview.....	14
4.2 General	14
4.3 Earthworks.....	15
4.4 Site Seismicity & Liquefaction Susceptibility	16
4.4.1 Site Subsoil Class.....	16
4.4.2 Peak ground acceleration for geotechnical analyses	16
4.4.3 Liquefaction Susceptibility.....	17
4.4.4 Liquefaction Effects.....	17
4.5 Soil Compressibility and Settlement Considerations	19
4.5.1 Overview.....	19
4.5.2 Settlement.....	19
4.5.3 Preliminary Settlement Analyses.....	20
4.5.4 Settlement Interpretation.....	20
4.6 Civil Infrastructure	21
4.6.1 Buried Services	21
4.6.2 Roads and Rail Siding.....	22
4.6.3 Yard Areas.....	22
4.6.4 Car parks	22
4.7 Ground Improvement Options	23
4.7.1 General	23
4.7.2 Ground Improvement Options	23
4.7.3 Ground Improvement Option Selection	26
4.8 Building Foundations and Floor Slabs.....	28



5. Further Work.....	30
6. Conclusions.....	31
7. Applicability.....	34
 Appendix A: Figures.....	
Appendix B: Geotechnical Factual Report.....	
Appendix C: Liquefaction Analysis Results.....	
Appendix D: Preliminary Settlement Analysis Results.....	



1. Introduction

1.1 Objective

This report outlines the findings of a geotechnical investigation undertaken for a site located at 231 Tahuna Road, Ohinewai and has been prepared in support of a proposed plan change application. Preliminary geotechnical analysis and interpretation has been undertaken to identify geotechnical engineering constraints and considerations for development of the land. Preliminary recommendations and options for ground improvements required to facilitate development of the site are presented.

The results of the geotechnical investigations are presented in a standalone factual geotechnical investigation report which is attached as Appendix B. The scope of geotechnical investigations undertaken to date is considered appropriate for a high level, planning assessment, however, further stages of investigation will be essential to support specific future development at the site.

1.2 Background and Proposed Development

Ambury Properties Limited, the property holding associate of the New Zealand Comfort Group Limited (NZCG), is proposing to develop land on the corner of Lumsden Road and Tahuna Road, Ohinewai (Allotment 405, Lots 1 and 2 DPS 29288 and Lots 2-3 474347). The property is zoned Rural in the operative and proposed Waikato District Plans. The proposed development - 'Sleepyhead Estate' will be a mixed-use, master-planned community located adjacent to the Waikato Expressway and the North Island Main Trunk railway at Ohinewai.

The proposed NZCG 100,000m² factory will be the major industrial anchor for the project. It will be accommodated in a 66ha industrial hub with rail siding access from the North Island Main Trunk railway. The project will also include 8.5ha of commercial development including a service station, local convenience stores and factory outlet shops. Thirty-three hectares of residential land for approximately 1100 new houses will also be provided, together with about 60ha of public open space.

Ambury has lodged a submission on the proposed Waikato District Plan requesting that the land be rezoned to a mix of industrial, residential and business zone to accommodate the mixed-use community. To support the proposed rezoning, Ambury is also seeking to embed a structure plan for Ohinewai within the District Plan. The structure plan will provide a framework for the development of the wider site, outlining the location of activities, the indicative road network and the general location of the green spaces that will provide for recreation and the management of stormwater.

The conceptual site layout plan¹, dated 3 October 2019, for the proposed Sleepyhead Estate is attached in Appendix A.

¹ Adapt Studio Ltd: Framework; Ohinewai Development, Illustrative Masterplan, Drawing 1805-018, dated 3 October 2019, Rev J.



2. Project Site

2.1 Location

The site is located on the eastern side of State Highway 1, at 231 Tahuna Road and Balemi Road, Ohinewai. The total site area is approximately 178 ha and is made up of the properties legally described as; Allotment 405, Whangamarino Parish (~37 ha), Lot 1, DPS 29288 (~68 ha), Lot 2, DP 29288 (~61 ha), Lot 3, DP 474347 (~11 ha) and Lot 2, DP 474347 (~0.8 ha). The location of the site and the individual property boundaries are presented in Figure 2-1 below.




Figure 2-1: Site location and boundaries

2.2 Description

The site is presently almost completely grass covered and is used for agricultural purposes. It is bounded by Tahuna Road to the south, Balemi Road and other agricultural land to the north, Department of Conservation land (including Lake Rotokawau) to the east, and Lumsden Road to the west.

The land is typically low lying and flat except for a ridgeline on the southern boundary (which Tahuna Road has been formed on) and two “spurs” which run in a north-south direction through the two southern properties (Lots 1 and 2, DP 29288). With reference to Figure 529-001 attached in Appendix A, ground surface elevations vary between approximately RL 20 m on the southern boundary with Tahuna Road and RL 6 m at the far eastern end of the site. Except for the localised ridge and spurs, the general site grade falls very gently from west to east.

The Waikato River is located approximately 1 km to the west of the site.

2.3 Published Geology

The published geological map (Figure 2-2 below and Figure 529-002 in Appendix A) shows the site sits over two surface geological formations, both members of the Tauranga Group. The Tauranga Group includes a range of marine, estuarine and terrestrial sediments deposited primarily during the Quaternary in the Bay of Plenty, Waikato and Auckland regions.

The bright yellow formation shown on Figure 2-2 is described on the Published Geological Map (1:250,000 – GNS Geomaps) as Tauranga Group, early to middle Pleistocene Age pumiceous river deposits comprising highly weathered, coarse pumiceous and rhyolitic sands and current-bedded grits, with interbedded peat and local gravels.

The pale-yellow material is also defined on the geological map (1:250,000 – GNS Geomaps) as Tauranga Group but a more recent (Holocene Age) deposit (last 2,000-10,000 years). This is described as comprising pumice sand, silt and gravel with peat beds.

The geotechnical investigation data for the site is consistent with the geological map.




Figure 2-1: Geological Map (Source GNS GeoMaps)

3. Geotechnical Investigations and Subsurface Conditions

3.1 General

Preliminary advice presented in this report is based on an early stage geotechnical investigation comprising a limited number of fully cored machine boreholes, Cone Penetration Tests, and Test Pits completed across the site between September 2018 and July 2019. Investigation locations were selected by Initia to provide an overview of the ground conditions across the entire site (tests spaced at approximately 250m centres where possible). A geotechnical investigation plan showing the locations of the investigation works completed is presented on Figure 529-01 in Appendix A.

In addition to the recent investigations, Initia has sourced the results of historical investigations undertaken for a proposed Ohinewai Opencast Coal Mine in 1986² (refer to the Geotechnical Factual Report in Appendix B).

The results of all available investigations have been used to develop a preliminary ground surface model. However, it should be noted that the nature and continuity of the ground conditions away from the test locations is inferred and it should be appreciated that actual conditions may vary away from the test locations.

3.2 Site Stratigraphy

The results of the geotechnical investigations indicate the site is underlain by variable Tauranga Group soils. The Tauranga Group encompasses highly variable soil types which are subdivided into different 'formations' of increasing age. These are;

- I. Taupo Pumice Alluvium (sourced from the Taupo eruption circa 50 AD);
- II. Rotokawau Formation (informal name assigned by the authors of the Ohinewai Open Cast Coal Mine investigation reports and adopted in this report)
- III. Karapiro Formation
- IV. Puketoka Formation
- V. Whangamarino Formation

The Whangamarino Formation was encountered at a depth of between 30 and 55 m below ground level in the Ohinewai Coal Mine investigations but was not encountered during the recent CPT and borehole investigations for this project (max investigation depth 25 m). As this material was not investigated, it is not referenced extensively in this report, however, it is understood to comprise Pliocene Age silty CLAY and clayey SILT with layers of PEAT, SAND and GRAVEL.

As it was not possible to determine the difference between the Karapiro Formation and Puketoka Formation units from the investigations completed to date (mainly CPTs), these two units, of similar Age and engineering properties, have been grouped together for the purposes of reporting and preliminary analyses.

The historical geotechnical investigations undertaken for the proposed Ohinewai Opencast Coal Mine show that the Tauranga Group soils extend to depths of approximately 60 to 110 m below ground level. The underlying unit is the Te Kuiti Group which comprises interbedded layers of siltstone, sandstone, claystone and coal measures. As the Te Kuiti Group is well below the depth of specific investigation for this project and likely of minor engineering relevance to the development proposed at

²State Coal Mines: Ministry of Energy; Ohinewai Opencast Feasibility Study; Geotechnical Investigations Phase II, December 1986, Volume 1 and Volume 2, prepared by RWL Mining Consultants

the site, this material type is not discussed further in this report except as to reference the depth to 'bedrock'.

A summary of the geology and material types present at the site is outlined in Table 3-1 below.

Table 3-1: Overall summary of geology and site stratigraphy at the Ohinewai site

Group	Formation	Generic Description	Age	Typical thickness (m)
Tauranga Group	Taupo Pumice Alluvium	Fine to medium SAND, Sandy SILT	~ 2000 years	0 to 3
	Rotokawau Formation	PEAT, Clayey SILT and silty CLAY	< 20,000 years	0 to 10
	Karapiro Formation	Fine to coarse SAND with common gravel beds	Pleistocene	20 to 40 (combined thickness)
	Puketoka Formation	Interbedded SILT, medium to coarse SAND, pumiceous GRAVEL and PEAT		
	Whangamarino Formation	Silty CLAY and clayey SILT with layers of PEAT, SAND & GRAVEL	Pliocene	30 to 80

The Taupo Pumice Alluvium and Rotokawau Formations are surficial deposits that occupy low-lying areas. The Taupo Pumice Alluvium is predominantly a pumiceous silty sand which is commonly between 1 and 3 m thick. The Rotokawau Formation is dominated by thick peat and is underlain by very soft silts and clays.

The Karapiro and Puketoka Formations vary considerably in grain size and composition but generally comprise silt, silty SAND, gravel and some peat.

The results of the investigations indicate that the Karapiro and Puketoka Formation materials form a 'paleo-topographic' surface at the site, with very recent infilling by the Rotokawau Formation "swamp" deposits and the Taupo Pumice Alluvium. The elevation of the 'paleo-topographic' Karapiro/Puketoka Formation unit is interpreted to sit between RL 9 and RL 20 m, i.e. the Karapiro/Puketoka Formation unit generally occurs at ground surface level over the higher parts of the site (above RL 9 m). The upper few metres of the Puketoka/Karapiro Formation is typically dominated by silty SANDs and sandy SILTs. The lowest parts of the site (surface levels of RL 7.5 m and lower) are usually dominated by greater thicknesses of the Rotokawau Formation.

The following tables outline the approximate depth and layer thicknesses of the relevant geological units at each of the five properties; Allotment 405 (north west site), Lot 2 DPS 28288 (south west site), Lot 1, DPS 28288 (south east site) and Lots 2 & 3 DP 474347.

Table 3-2: Allotment 405 – Site Stratigraphy

Surface levels	Taupo Pumice Alluvium		Rotokawau Formation		Puketoka Formation & Karapiro Formation	
	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)
“High” Ground Surface elevation > RL 9.0	-	0	-	0	0	> 20 m
“Intermediate” Ground Surface elevation < RL 9.0, > RL 7.5	0	1.0 to 4.0 [2.5]	1.0 to 4.0	1.0 to 4.0 [1.5]	3.8 to 5.7 [5]	> 20 m
“Low” Ground Surface elevation < RL 7.5	0	1.5 to 4.0 [2]	1.5 to 4.0	6.0 to 10 [8]	10.3 to 11.5 [10.5]	> 20 m

1. Bracketed values indicate average thickness

Table 3-3: Lot 2, DPS29288 – Site Stratigraphy

Surface levels	Taupo Pumice Alluvium		Rotokawau Formation		Puketoka Formation & Karapiro Formation	
	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)
“High” Ground Surface elevation > RL 9.0	-	0	-	0	0	> 20 m
“Intermediate” Ground Surface elevation < RL 9.0, > RL 7.5	0	1.5 to 3 [2]	1.5 to 3	1.5 to 4 [2]	3.0 to 6.0 [4]	> 20 m
“Low” Ground Surface elevation < RL 7.5	0	0.5 to 3.0 [1.0]	0.5 to 3.0	7 to 9 [8]	9.2 to 10.7 [10]	> 20 m

1. Bracketed values indicate average thickness

Table 3-4: Lot 1, DPS29288 – Site Stratigraphy

Surface levels	Taupo Pumice Alluvium		Rotokawau Formation		Puketoka Formation & Karapiro Formation	
	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)
“High” Ground Surface elevation > RL 9.0	-	0	-	0	0	> 20 m
“Intermediate” Ground Surface elevation < RL 9.0, > RL 7.5	No tests performed in this elevation range					
“Low” Ground Surface elevation < RL 7.5	0	0 to 3.0 [0.5]		5.5 to 13.5 [8.0]	6.5 to 13 [9.0]	> 20 m

1. Bracketed values indicate average thickness



Table 3-5: Lots 2 and 3, DP 474347 – Site Stratigraphy

Surface levels	Taupo Pumice Alluvium		Rotokawau Formation		Puketoka Formation & Karapiro Formation	
	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)	Depth (m)	Thickness (m)
“High” Ground Surface elevation > RL 9.0	-	0	-	0	0	> 20 m
“Intermediate” Ground Surface elevation < RL 9.0, > RL 7.5	0	1.0 to 3.0 [2.1]	1.0 to 3.0 [2.0]	0 to 10.4 [3.0]	4.0 to 13.0 [5.0]	> 20 m
“Low” Ground Surface elevation < RL 7.5	No tests performed in this elevation range					

1. Bracketed values indicate average thickness

3.3 Test Results

Tables 3-5 and 3-6 below present a summary of in situ test results from the recent investigations and laboratory testing from historical geotechnical investigations. There is extensive additional laboratory test data from the Ohinewai Opencast Coal Mine investigations; Table 3-6 reports only the results considered pertinent to the plan change assessment of the site.

Table 3-5: In situ test results – Recent Investigations

Geological Unit	Formation	In situ strength parameters – range & [25 th percentile]	
		SPT ‘N’	CPT q _c (MPa)
Tauranga Group	Taupo Pumice Alluvium	4* [4]	1.5 to 6.0 [2.5]
	Rotokawau Formation	0 - 2 [0]	0.05 to 0.4 [0.15]
	Karapiro Formation and Puketoka Formation	4-31 [9]	0.5 to 15 [2.0]

* Single test result



Table 3-6: Laboratory Test Results – Ohinewai Opencast Coal Mine Investigations

Soil type	Laboratory Test Results – Range and [mean]								
	Bulk density (t/m³)	Dry Density (t/m³)	Water content (%)	Undrained Shear Strength (kPa)	Atterberg Limits			Mv m²/MN	Cv m²/yr
					LL	PL	PI		
Rotokawau Formation – Clay/Silt/Peat			120-240 [160]	0.8-20 [8.5]				1.8 to 2.5	0.44 to 16
Karapiro Formation SAND	1.37-2.35 [1.73]	0.74-2.01 [1.24]	15-85 [42]	-	-				
Puketoka Formation Clay/Silt	1.34-1.90 [1.66]	0.64-1.39 [1.08]	29-115 [55]		40-180 [79]	21-86 [38]	19-91 [41]	0.28	11 – 29
Puketoka Formation Sand	1.32-2.71 [1.70]	0.58-2.06 [1.16]	8.4-109 [48]	-	-	-	-		



3.4 Groundwater

During the Initia investigations, groundwater was encountered at a depth of 0.5 to 1.5 m below ground level in the 'Intermediate ground' areas (RL 7.5 to 9 m) and at near surface levels in the "Low ground" areas of the site (RL 6.0 to 7.5 m). The groundwater measurements were taken from CPTs and the three machine boreholes only and are therefore not considered to provide a reliable measure of groundwater levels and variance across the site.

Based on the results of investigations, and observations of ground surface saturation at the time of investigation, groundwater levels are expected to vary between RL 7 m and RL 6 m across the majority of the site. Higher levels may be present around the ridge at the southern and southwestern boundaries and the two north-south "spurs" where ground surface elevations are as high as RL 20 m. Further monitoring would be required to confirm this.

Regional groundwater levels are expected to be controlled by the Waikato River (to the west) and Lake Rotokauwau (to the east).

For detailed geotechnical analyses purposes, groundwater should be assumed to be at 0.5 m depth where site levels are at RL 7.5 m or higher and at ground surface level where the site levels are below RL 7.0 m.

4. Geotechnical Considerations for Development

4.1 Overview

The site is underlain by recent (Holocene Age) alluvial soils which are susceptible to liquefaction (ULS seismic events) and are highly compressible. These materials extend to depths of up to 15 m below ground level. The underlying Pleistocene Age (Puketoka Formation and Karapiro Formation) soils are less compressible but may still be susceptible to liquefaction. The geotechnical conditions at the site are variable depending on their location within the proposed parcel boundaries and will present significant engineering challenges for development of the land.

From the results of investigations completed to date, several areas of the site have been identified with challenging ground conditions. This is predominantly land that is underlain by significant thicknesses of the Rotokawau Formation (containing highly compressible peat and other very soft soils). Reference should be made to Figure 529-004 in Appendix A which zones land according to 'settlement' magnitudes resulting from an assumed uniform surcharge applied over the entire site. Development over areas of the site zoned red on Figure 529-004 (settlements > 500 mm) will be therefore be highly constrained. For this reason, the Masterplan for the site largely excludes future development in this zone (refer Adapt Studio, Rev J presented in Appendix A).

The remainder of the site is generally considered suitable for development and the construction of commercial and residential buildings and associated infrastructure. However, the land has been identified as having a high liquefaction severity number (LSN) due to the presence of surface alluvial sands and also as moderately to highly compressible when loaded. Therefore, ground improvements will be required over most of the site to support for future building development.

The advice presented in this report is intended to support the plan change application only. Further geotechnical investigations and analysis are essential for the subdivision and for specific building developments on the site.

4.2 General

Based on our understanding of the proposed development detailed in the Illustrative Masterplan (Adapt Studio, Rev J) and our knowledge of the geology and local ground conditions, the principal geotechnical considerations for development of the site are as follows;

- Earthworks and cut/fill to form level building platforms;
- Liquefaction susceptibility and consequential effects during and following seismic events;
- Settlement of compressible soils due to placement of new fill and/or future buildings loads;
- Installation/construction of civil infrastructure such as three water services (stormwater, sewer and water main), internal roads and yard areas, the rail siding, car parking etc;
- Ground improvements to address liquefaction and settlement risks;
- Foundation for new buildings – light industrial to residential;

The above geotechnical considerations are discussed in the following subsections.

As the investigations undertaken and discussed in this report have been completed to provide an overview of the site conditions to assess and support a planning change application, further geotechnical investigations, geotechnical analysis and detailed design will be required to support any specific development of the land.

4.3 Earthworks

As outlined in Section 2.2, the site is typically flat to gently sloping except for the ridge along the southern boundary and the two spurs which run approximately north-south through the centre of the site. Design surface levels for the site are expected to range between RL 10 m at the western most edge of the site and RL 7 m at the eastern end of Lot 1, DPS 29288. It is anticipated that overall site grades would be east and north east, with possible stormwater treatment at the eastern end of Lot 1, DPS 29288. The following earthworks are expected to be required to facilitate development;

- i. Cuts to lower the north-south trending “spurs” which are presently as high as RL 16 m. Cut depths may be as much as 6 m at localised ‘high-points’ but with a typical depth of 2 to 4 m.
- ii. Re-grading of the “ridge” that runs along the southern boundary of the site. These works are expected to comprise cuts of up to about 5 - 6 m depth but generally 2-3 m depth to form more uniformly sloping ground or terraces suitable for future buildings.
- iii. Placement of fill between the existing “spurs” and over the north western corner of the site (Allotment 405) to provide a gently sloping grade (approximately 1%) to the north and east.
- iv. Possible construction of swales along the northern boundary of Lot 3 DP 474347 and Lots 1 and 2 DPS 29288 to convey stormwater and overland flows to the east for treatment before being discharged into Lake Rotokawau.

The key earthworks considerations are summarised below;

- Cuts extending below RL 7 in the west and below RL 6.0 in the east will almost certainly encounter groundwater. As the upper soils at the western end of the site are predominantly sandy, groundwater inflows are expected to be significant and difficult to control. This is particularly relevant for installation of buried services (see Section 4.6 below).
- The upper silty sands (Taupo Pumice Alluvium) are likely to be suitable for re-use as engineered fill. Sand dominated material can usually be compacted to an engineered standard, even at relatively high water contents. If the soils are ‘silt’ dominated (>35-40%) they may need to be conditioned (dried-back) prior to placement.
- Lime and cement stabilisation of the upper soils may be required to provide increased strength to the fill and to mitigate the risk/effects of liquefaction from a ULS seismic event (see Section 4.4 below).
- Excavations through the southern “ridge” and the two north-south trending “spurs” are expected to extend through a mixture of sands and silts which could be used (likely with some conditioning) for engineered fill. Excavation in these areas of the site will result in some surface unloading (“load compensation”) for future building platforms, i.e. the risk of settlement, due to future building loads, may not need to be mitigated in these areas.
- For the lower lying areas of the site (below RL 9.0 m), excavations which extend below the surface “crust” of silty sand (Taupo Pumice Alluvium) which varies between 0.5 m and 4.5 m in thickness, will encounter very soft clay/silt or peat (Rotokawau Formation) with undrained shear strengths as low as 5-10 kPa. This material is very unlikely to be suitable for re-use as engineered fill and will not support earthmoving or construction traffic.
- It is recommended that a minimum 800 mm to 1,000 mm thickness of the Taupo Pumice Alluvium layer, where underlain by Rotokawau Formation, is left in situ to support earthworks plant and compaction of new fill. Alternatively, a minimum 500 mm thick layer of Soft Pit Run (SPR) will be required to form a “working platform” to enable compaction of subsequent layers over the top of the Rotokawau Formation. At the eastern end of the site (Lot 1, DPS29288), the Taupo Pumice Alluvium layer is as thin as 300 mm; therefore a working layer of SPR or similar may need to be formed over the subgrade prior to placing any new fill.
- Allowance should be made for significant volumes of “unsuitable” soil which is likely to be encountered across the entire site. Further investigation will be required to determine the spatial extent of unsuitable soils.

- Allowance should be made for importation of significant volumes of fill from off-site to lift ground levels above existing site levels (there is unlikely to be enough fill available from designated “cut” areas). Imported fill should preferentially be cohesive soils and/or SPR (completely to highly weathered rock, usually quarry over-burden).
- Placement of new fill will initiate settlement of the underlying soils which may take several months or more to complete (see Section 4.5 below). Monitoring of settlement magnitudes and rates will be required. The ground will also need to be over-filled to account for settlement of the deeper soils, i.e. so that design surface levels are achieved following completion of the settlement process.

4.4 Site Seismicity & Liquefaction Susceptibility

4.4.1 Site Subsoil Class

With the exception of the southern ridge line and the two north-south “spurs” (high ground, RL > 9.0 m), the site is underlain by between 1 and 14.5 m thickness of very soft soil (Rotokawau Formation) with an undrained shear strength of < 12.5 kPa. These soils are underlain by moderate strength clays/silts, silty sands and peat of the Karapiro and Puketoka Formations to the full depth of investigation (25 m below ground level). Rock (Te-Kuiti Group siltstone, claystone, sandstone) is inferred from a depth of approximately 100 m below ground level based on historical investigation data at the south eastern end of the site.

Where there is more than 10 m of Rotokawau Formation underlying the site in the low lying areas (typically < RL 7.5m), a seismic subsoil Class E – soft soil site – should be assumed in accordance with NZS 1170.5. Parts of the site (areas with a ground surface elevation higher than RL 9.0 m, where the Rotokawau Formation layer is absent or less than 10 m thick) could be re-classified as Class D – deep soil site – during subsequent stages of investigation. However, there is presently insufficient data available to delineate where Class D versus Class E conditions prevail.

For geotechnical analysis purposes, there is no difference in the Peak Ground Acceleration for a Class D and Class E site.

4.4.2 Peak ground acceleration for geotechnical analyses

The peak ground acceleration for the site – both SLS and ULS design cases - has been derived based on NZS1170.5 and the NZTA Bridge Manual assuming the parameters outlined in Table 4-2 below.

Table 4-2: Seismic parameters for derivation of site PGA

Design assumption	Parameter
Building Importance Level	IL2 (typical commercial/industrial building assumed, <u>to be confirmed by designer</u>) – assumes less than 5,000 people within the building
Building design life	50 years (assumed, <u>to be confirmed by designer</u>)
Return Period	500 Years – ULS Event (Table 3.2, NZS 1170.5)
Near Fault Factor	1.0 (distance to nearest fault > 20 km)
Site subsoil class	E (soft soil site, as above)
Site subsoil class factor	1.0 (Table 3.2, NZS 1170.5)

Assuming the above parameters, design peak ground accelerations (PGAs) and earthquake magnitudes are as follows.

- SLS – 25 Year Annual Exceedance Probability: PGA = 0.05g, Magnitude 5.8
- ULS – 500 Year Annual Exceedance Probability: PGA = 0.22g, Magnitude 5.8

4.4.3 Liquefaction Susceptibility

Liquefaction susceptibility analyses have been undertaken using the results of the site-specific Cone Penetration Tests (CPTs) applied to the analysis method presented by Boulanger and Idriss (2014). The CPTs were analysed for both the SLS (25-year AEP) and ULS (500 year AEP) seismic events as outlined above. A groundwater level of 0.5 m below current ground level was assumed for consistency in assessing liquefaction susceptibility site wide.

The results of the analyses indicate that there is a negligible risk of liquefaction occurring during a SLS seismic event. However, for the Ultimate Limit State (ULS) event, there is a very high likelihood of liquefaction occurring from near surface levels over most of the site. This is because the site is largely underlain by fully saturated, sand-dominated soils from near surface levels (Taupo Pumice Alluvium) and the underlying Karapiro/Puketoka Formation which extends to the full depth of investigation. The majority of the site is therefore considered to be susceptible to liquefaction to depths greater than 25 m below ground level. The Rotokawau Formation (peat and soft clays/silts) is not susceptible to liquefaction as it is dominated by clays, silts and peat.

Results of the liquefaction susceptibility analyses undertaken for the ULS seismic event (PGA = 0.22g) are attached in Appendix C.

4.4.4 Liquefaction Effects

Liquefaction can affect land and development in the following ways:

- Ejection of sand/silt boils to ground surface level;
- Deformation and rupture of pavements;
- Flotation of manhole risers and buried services, including rupture of pipes which move differentially;
- Total and differential settlement of building structures and floor slabs, possibly resulting in structural collapse;
- Lateral spreading towards an unsupported face, e.g. coastline, river bank etc

An important factor in controlling the effects of liquefaction is the “crust thickness”, i.e. the thickness of non-liquefiable soils (e.g. soils above groundwater level or soils which are not susceptible to liquefaction such as gravels and clay/silt dominated soils) that overly liquefaction susceptible soils. Experience from the Canterbury sequence of earthquakes has shown that the effects of liquefaction on buildings, pavements and services are largely mitigated for land which has a crust thicknesses greater than 3 m.

The Liquefaction Severity Number (LSN) is an index which was developed following the Canterbury Sequence of earthquakes and relies on data from a large database of land and dwelling damage. The LSN accounts for the cumulative thickness of liquefaction, the degree of liquefaction, crust-thickness, and the depth at which liquefaction occurs. It is a useful index for categorising the effects of liquefaction for differing ground conditions and variability in soils – both spatially and in elevation. A description of the expected effects of liquefaction – assigned LSN values ranging between 1 and >50 – is presented in Table 4-3 below.

Table 4-3: Liquefaction Severity Number (LSN) and observed effects

LSN Range	Predominant Performance
0 -10	Little to no expression of liquefaction, minor effects
10 -20	Minor expression of liquefaction, some sand boils
20 -30	Moderate expression of liquefaction, with sand boils and some structural damage
30 -40	Moderate to severe expression of liquefaction, settlement can cause structural damage
40 -50	Major expression of liquefaction, undulations and damage to ground surface, severe total and differential settlements of structures
> 50	Severe damage, extensive evidence of liquefaction at surface severe total and differential settlements affecting structures, damage to services

The results of the preliminary liquefaction analyses undertaken as part of this site wide geotechnical assessment indicate that parts of the site (those areas underlain Taupo Pumice Alluvium and Karapiro/Puketoka Formation) have a Liquefaction Severity Number > 50 (typically between 60 and 100), i.e. severe damage could be expected to buildings and infrastructure at ground surface level. Almost all of Allotment 405 (north western end of site) and approximately half of Lot 2 and 3 DP 474347 and Lot 2, DPS 29288 (south western end of site), are at risk of severe damage should a ULS seismic event occur. By contrast, the majority of Lot 1, DPS 29288 (south eastern end of site) is expected to have little to minor expression of liquefaction following a ULS seismic event (LSN values less than 15). This is because the eastern end of the site is almost directly underlain by the very soft Rotokawau Formation clays/silts and peat that are not liquefaction susceptible. Figure 529-003 attached in Appendix A presents the predicted LSN for each CPT and zoning of the site depending on the LSN range.

Ground improvements will therefore be required over the majority of the site to ensure that there is at least 3 m of non-liquefiable material ("crust thickness") beneath the floor slab of any future building and a minimum of approximately 2.5 m below the underside of any shallow foundations. This is to address "life-safety" requirements for ULS design, i.e. to ensure that there is no structural collapse of the buildings that could result in loss of life. Distortion and cracking of the floor slabs, and possible differential settlement/distortion of the structure, could still occur. However, it is generally accepted that such damage could either be repaired if it cost effective to do so, or alternatively, that the structures would be demolished and re-constructed. Greater resilience can be considered, if required, to maintain full serviceability of the building following a ULS seismic event. However, this would usually involve significant additional cost associated with a greater depth of ground improvement. Further detail on ground improvement options is outlined in Section 4.7.

Though not required for life-safety purposes, it is recommended that consideration be given to providing resilience to liquefaction for roads, rail sidings, and other pavements such as yards. This could be limited to simply ensuring that there is a non-liquefiable "crust" of at least 1 m beneath pavements. Buried services would need to be detailed to accommodate significant differential settlements and to resist buoyancy pressures for manholes and other below ground structures.

4.5 Soil Compressibility and Settlement Considerations

4.5.1 Overview

The Ohinewai site is underlain by a sequence of compressible geological units. The Rotokawau Formation, in particular, is highly compressible as it is comprised of interbedded layers of PEAT and very soft clayey SILT and silty CLAY with undrained shear strengths less than 10 kPa.

Settlement will occur at the site as a result of one or more of the following activities which will likely be required as part of the development of the land for use as commercial and/or residential;

1. Placement of new fill above present ground levels. For every 1 m of new bulk fill placed and compacted to an engineered standard, the equivalent surcharge pressure would be approximately 17-20 kPa.
2. Construction of building floor slabs including the underlying pavement formation, i.e. the “dead load” of the slab. This would usually include approximately 6 kPa for a 300 mm thick layer of subbase/basecourse and approximately 4 kPa for the floor slab (175 mm thick), i.e. a total of 10 kPa “dead load”.
3. Distributed “live load” acting on the floor slab, e.g. racking for storage purposes. The majority of new light industrial/warehouse buildings are detailed for a peak floor slab live load of 35 kPa which usually equates to approximately 25 kPa fully distributed live load, taking account of aisle widths and uneven load distribution.
4. Concentrated pressures directly beneath shallow foundations supporting the building structure (typically 50-100 kPa, serviceability stress).
5. Dewatering of soils (lowering of the groundwater level below historical levels) resulting in an increase in vertical effective stress (reduced “buoyancy” between soil particles).

4.5.2 Settlement

Total settlement is the combination of three different types of settlement;

- **Elastic settlement.** This is settlement which usually occurs instantaneously due to shear deformation following loading (within hours/days). Elastic settlement is usually greatest in granular soils (gravels/sands) as the soil particles are densified/re-ordered on loading.
- **Consolidation settlement.** This occurs as pore-water is gradually squeezed out of the soil matrix, allowing the void space previously occupied by water to “collapse”, thereby densifying the soil. Consolidation settlement is usually the largest component of total settlement and can be the most difficult to quantify. The time taken for consolidation settlement to complete (usually referred to as the point at which 90% of the theoretical maximum consolidation settlement has occurred) is dependent on the permeability of the soil, the thickness of the compressible layer and the drainage distance to the top/ bottom of the layer, e.g. a 1 m thick layer of sandy silt with high permeability underlain by gravel will consolidate exponentially faster than a 10 m thick layer of clay with very low permeability.
- **Secondary compression (creep);** Secondary compression or “creep” settlement can occur over long periods of time (i.e. over the full design life of the structure). This process is usually caused by creep, a viscous behaviour where the soil particles/grains become so closely packed they start to plastically deform themselves and/or by long-term degradation of organic matter in organic soil types. Secondary compression is a significant risk where peat and very soft soils exist (e.g. the Rotokawau Formation). Secondary compression can be as much as 20% of the total settlement for normally consolidated soils.

4.5.3 Preliminary Settlement Analyses

Preliminary settlement analyses have been undertaken to assess the potential magnitude of total settlement assuming the following potential surface loading;

- | | | |
|------|--|---------------|
| i. | Bulk earthworks filling, up to 1 m in height | 20 kPa |
| ii. | Building floor slab dead load: | 10 kPa |
| iii. | Building floor slab - distributed live load: | <u>15 kPa</u> |

Total gross applied pressure: **45 kPa**

In some cases, the height of bulk filling will be considerably greater than 1 m, particularly in the low lying areas of the site, toward the eastern end of Lot 1 DPS 29288, needing to be lifted to the design subgrade levels for flooding/overland flow requirements, however, this assumed fill height has been applied uniformly to allow direct comparison of the settlement potential/ variability across the site.

The preliminary settlement analyses were undertaken using the geotechnical analysis software package, CPeT-IT which relies on published correlations between Cone Penetration Test results with the constrained modulus of the soil. The results include a component of secondary compression which is greatest in the Rotokawau Formation unit.

The results of the preliminary settlement analyses are presented on Figure 529-004 in Appendix A. In general, the predicted total settlements for a surcharge pressure of 45 kPa, vary between 25 mm to 80 mm in areas directly underlain by Karapiro/Puketoka Formation in the south and west of the site and beneath the two prominent spurs. These settlement estimates increase to greater than 2,000 mm where the thickness of the Rotokawau Formation unit is approximately 10 m (eastern end of Lot 1, DPS29288).

For comparison purposes, a simple one-dimensional calculation (ignoring depth influence factors) has been undertaken using the M_v values measured in laboratory testing (site specific and for the Ohinewai Opencast Mine investigations ($M_v = 1.0$ and $3.5 \text{ m}^2/\text{MN}$ for the Rotokawau Formation) and assumed values of $M_v = 0.1$ to $0.3 \text{ m}^2/\text{MN}$ for Karapiro/Puketoka Formation).

Consolidation settlement magnitudes within the Rotokawau Formation are expected to range between approximately 50 and 150 mm per 1 m layer thickness (for a 45 kPa surcharge pressure). Similarly, assuming M_v values of 0.1 to $0.3 \text{ m}^2/\text{MN}$ for the Karapiro/Puketoka Formation, settlements are expected to be approximately 5 mm to 15 mm per metre thickness (45 kPa surcharge). Considering, for example, the inferred ground conditions at the location of CPT40 (8 m thickness of Rotokawau Formation and 6 m of Karapiro/Puketoka Formation for a total CPT depth of 14 m), the total consolidation settlement could be expected to be in the range of 450 mm to 1300 mm. This compares well with the predicted total settlement of 700 mm using CPeT-IT. It is noted that the actual settlement at this location could be 100 to 300 mm greater depending on the actual depth of compressible soils within the Karapiro/Puketoka Formation unit extending below the investigation depth.

Available laboratory test data indicates that the Rotokawau Formation is approximately 10 to 20 times more compressible than the Karapiro/Puketoka Formation soils. Therefore, wherever the Rotokawau Formation soils are present, some form of ground improvement will be required to reduce settlement magnitudes and/or to address settlement effects. Where the underlying thickness of the Rotokawau Formation soils is in excess of 4-5m development on this land will likely be challenging and constrained.

4.5.4 Settlement Interpretation

As illustrated on Figure 529-004, the majority of the site, excluding the "high ground" areas where the ground surface elevation is greater than approximately RL 9.0 m (directly underlain by Karapiro/Puketoka Formation soils), is considered to be moderately to highly compressible (200mm to

>500mm estimated settlement). Areas of the site which have predicted settlements greater than 50-80 mm (for a 45 kPa surcharge) will likely require some form of ground improvement/treatment to reduce settlement magnitudes and/or mitigate the effects of settlement. Ground improvement options are presented in Section 4.7.

Most of Lot 1, DPS 29288 at the east of the site is considered to be highly compressible with predicted settlements ranging between approximately 800 mm and > 2,000 mm. This is also the case at the far eastern end of Allotment 405 and the central part of Lot 2 DPS 29288 where predicted settlements are typically in excess of 500mm. Therefore, it may not be practical to develop these areas of the site and this is reflected in the designation of these areas in the Illustrative Masterplan (Adapt Studios, Rev J) for use as vegetated areas with wetlands and very minor levels of development (small lightweight structures, paths, sports fields and gardens).

Long-term, secondary compression or “creep” settlement is likely to occur in large areas of the site, following completion of consolidation settlement. Such settlements could occur over the design life of the structure (50 years or more) if not addressed as part of ground improvements and/or allowed for in design and detailing of buildings and pavements.

Post-construction total settlements can be tolerated to some degree, provided that differential settlement magnitudes are minimised to no more than approximately 1 in 250 (e.g. up to 50 mm settlement over a distance of 12.5m could be accommodated by appropriately detailed floor slabs and most structures). Settlement tolerant structures (e.g. steel portal frames) and flexible cladding systems (e.g. timber) should also be considered.

Areas of high ground which are cut down to form gently graded land (approximately 1%) or terraced building platforms will be load compensated by the weight of soil removed, e.g. ground with a present surface elevation of RL 13.0 m cut to a design subgrade level of RL 10.0 m will be load compensated by as much as $3 \text{ m} \times 17 \text{ kN/m}^3 = 51 \text{ kPa}$. Thus, new buildings constructed in this situation will experience significantly reduced settlements. These areas should be carefully surveyed prior to and following earthworks so that compensation effects can be assessed, and the scope of ground improvement works rationalised (noting that liquefaction susceptibility may still need to be addressed in these areas).

4.6 Civil Infrastructure

To prepare the site for light industrial, commercial, retail and possible residential development, it will be necessary to install internal roads, buried services (gravity fed services such as sanitary sewer and stormwater being of greatest relevance from a geotechnical perspective), car parking, yard areas and a rail siding off the North Island Main Trunk line. The following preliminary advice and comment is provided in relation to construction of new infrastructure at this site.

4.6.1 Buried Services

Groundwater levels at the site are high (near surface levels) and occur in combination with loose sand present from ground surface over the majority of the site, except the eastern end of Lot 1, DPS 29288. Excavating trenches or pits below groundwater level, for installation of buried services, is expected to be problematic due to the potential for “running sands” and unstable, low strength clays/silts. Therefore, wherever possible, it is advisable to limit the depth of buried services or alternatively to “lift” the site levels above groundwater level using cohesive soils or SPR. This would enable new services to be trenched and installed within new fill materials or maintained in the upper natural soils, above groundwater level. Where this is not practical, trenchless installation methods such as pipe thrusting should be considered for construction of buried services. Trench shields are unlikely to be suitable or safe, however, sheet piles could be considered.

As outlined in Sections 4.4 and 4.5, both seismic (liquefaction induced) and static (consolidation/creep) settlement may occur across large areas of the site. It is therefore recommended that gravity fed

services be specifically detailed with contingent drainage grade to accommodate localised sag in the pipelines. Flexible pipes (such as HDPE) and flexible joints/connections should also be used. Manholes and other below ground structures (e.g. buried tanks) should also be specifically detailed to resist buoyancy pressures from elevated groundwater levels and from liquefied soils following a ULS seismic event.

To mitigate the effects of static settlement due to placement of new fill during subdivision earthworks, it is recommended that buried services be installed following completion of consolidation settlement. This could be established by installing and monitoring settlement pins at ground surface level following earthworks completion.

Flexible service connections may be required where services enter new buildings, particularly where differing levels of ground improvement have been employed inside and outside of building footprints.

4.6.2 Roads and Rail Siding

New roads (trafficked by heavy and light vehicles) and the proposed rail siding are likely to traverse areas of the site underlain by poor ground conditions. As road and rail traffic is largely 'transient', long term consolidation and creep settlement from vehicle and train surcharging is unlikely to occur if the roads/rail are constructed close to current grade. However, improvements to the subgrade strength are likely to be required to support construction of road and rail pavements. A minimum 1 m thickness of stabilised or high strength subgrade (e.g. new engineered fill) is likely to be required to support future road and rail traffic. This will help raft out vehicle wheel loads and train loads and mitigate the effects of liquefaction should a ULS seismic event occur. Further comment is provided in Section 4.7 below.

Where light vehicle accessways are proposed to developments in the eastern area of Lot 1 DPS 29288 (access to sports fields, and market garden areas) these roads should be constructed with a minimal increase in ground level where possible. Should filling be necessary to create the required level, the road surface can be left unsealed, and left to settle for a period before being paved at a later date. An allowance should be made for future maintenance comprising releveling the accessway by patching or placement of a new surface layer on the pavement should significant surface deformation occur (likely 2-5 years) under loading. Alternatively, preloading of roads and rail siding could be considered to mitigate the risks.

4.6.3 Yard Areas

Areas of the site that are intended to be used for medium to long term storage (e.g. shipping containers stored adjacent to the rail siding and outside buildings) may require ground improvement to minimise settlements to acceptable limits and to mitigate settlement effects. Ground improvement options for heavily loaded yard areas are presented in Section 4.7 below, however, it is likely that yard areas with concrete pavements may need to be treated similarly to building floor slabs. Alternatively, the yard areas could be left unsealed (exposed unbound granular pavement surface) and left to settle for a period (likely years) before being sealed at a later date. Flexible pavement surfaces such as asphalt could also be considered and re-sealed/maintained as required if significant ground surface deformation occurs under loading.

4.6.4 Car parks

Areas of the site that are underlain by relatively low strength and highly compressible soils could be utilised for car parking (light vehicles). The surcharge imposed by vehicles is low and hence consolidation and long-term settlement of these areas would be expected to be minimal (assuming the ground is not lifted with fill). Provided that a reasonable subgrade (at least 800 mm of soil with a CBR > 3%) is present overlying the soft soils, car park pavements could likely be formed without any requirement for ground improvement.

4.7 Ground Improvement Options

4.7.1 General

As outlined above, some form of ground improvement is expected to be required beneath future building platforms, road carriageways, rail sidings, and yard areas. The selected ground improvement method will need to address one or more of the following geotechnical issues identified for this site;

- Liquefaction susceptibility of the near surface and deep subsoils. A minimum 3 m thick “crust” of non-liquefiable soils is required to support future buildings formed on grade to address ‘life-safety’ risk.
- Consolidation and secondary compression settlement effects due to the placement of new fill (to lift site levels), as well as building dead and live loads.
- Low strength subgrade conditions for construction of new pavements (rail siding, roads, yards floor slabs etc).

4.7.2 Ground Improvement Options

Table 4-4 outlines possible ground improvement options, pros and cons for each and a qualitative assessment of cost (low, medium or high).

Table 4-4: Ground Improvement Options

Ground improvement option	Details	Addresses risks from		Pros	Cons	Relative cost appraisal
		Liquefaction	Settlement			
Preloading	All building platforms and some pavements (those with medium to long term sustained heavy loading, e.g. yard storage areas, rail corridor, areas of fill embankment) could be preloaded with soil/rock (locally sourced or imported) and held for a period of 12-18 months. Regular monitoring of instrumentation required throughout preload period.	No	Yes	Usually the most cost-effective form of ground improvement for settlement where there is a readily available supply of preload material (on site or offsite). Preload material can be re-used for other buildings once initial preload is complete. Provides a uniformly improved platform which should be suitable for a shallow foundation/slab on grade solution for future buildings. Preload pressure can be designed to the equivalent long-term building surcharge pressure. Large open site, with limited space constraints, well suited to earthworks type operations.	Not a complete improvement option in isolation – ground will still require treatment to mitigate liquefaction effects. Preload timeframes are uncertain. May require importation of significant volume of preload material if no suitable on-site source is available (e.g. Soft Pit Run or GAP65). Secondary settlement (creep) likely to continue even after preloading and will need to be designed for.	Low
Stone columns/rammed aggregate piers	The ground beneath building platforms is improved by installation of columns of hardfill at a regular grid spacing. The columns are usually 600 mm to 1,000 mm in diameter and spaced in a triangular arrangement of 2D to 3.5D (D=column diameter), depending on the nature of the soils (a typical spacing of 2.5D should be assumed for this site). The columns are installed either by 'vibro-replacement' where aggregate is fed into the ground and vibrated by a probe that both densifies the natural ground (depending on the properties of the ground) and compacts the aggregate in the column. Alternatively, 'piers' can be installed by "ramming" aggregate in thin lifts from the base of the pier to ground surface level. In both cases, the result of this stabilisation method is the formation of a thick 'raft' that acts as a composite soil mass that fully translates and distributes building loads to the toe level of the piers/columns. Column/pier depths at this site could vary between 8 and 15 m depth. Stone columns and rammed aggregate piers are often used in combination with a reinforced gravel raft beneath building footprints to reduce the centre to centre spacing of the columns/piers and to help ensure the ground below the buildings behaves a uniform, composite founding material.	Yes (in the upper soils)	Partly	Provides a uniformly improved raft of ground suitable for supporting buildings on shallow foundation/slab on grade. Cost-effective when compared against traditional piled foundation options. Usually very effective method of ground improvement for sites which are largely dominated by sandy material. Large number of quarries located within 20 km of site.	There is no continuous and reliable end-bearing stratum for columns/piers to bear on. Therefore, settlement may still occur in the deeper soils, below the column/pier toe level. This could be mitigated by preloading. Requires significant volume of imported aggregate to construct columns/piers. Ground conditions are highly variable (peats, sands, clays etc) which could make installation problematic. The effectiveness of the stone columns will be variable due to the interlayering of sandy and silty deposits (meaning a relatively high density of columns is likely to be required) Some areas of the site may be too soft and compressible to confine stone columns when they are axially loaded. Soils at and below the toe level of the columns may be liquefiable under a ULS event which would result in loss of end bearing.	Medium
Deep soil mixed (DSM) columns	Similar concept to Stone Columns and Rammed Aggregate Piers; building loads are effectively supported by bearing on ground at a greater depth (8-15 m) by installation of regularly spaced soil/cement mixed columns, typically 600 mm to 1,000 mm in diameter. The difference between stone column/RAPs and DSMs is that DSMs involve in situ stabilisation of the natural soils by injection of cement (and/or other suitable binders) and mixing by auger to form a column of relatively high material (typically around 1 MPa compressive strength).	Yes (in the upper soils)	Partly	Provides a uniformly improved raft of ground for supporting building on shallow foundation/slab on grade. Cost effective when compared against traditional piled solutions Avoids requirement to import large volume of granular material, as with stone columns/RAPs.	No continuous and reliable end bearing stratum for DSMs to bear on. Therefore, settlement may still occur in the deeper soils below the DSM toe level. This could be mitigated by preloading. Requires significant volume of cement for binding the soils. May be difficult to achieve a uniform/consistent column strength due to variable soil types (sands/clays/peats). Peat may not bind with cement. Soils at and below the toe level of the columns may be liquefiable under a ULS event which would result in loss of end bearing.	Medium
Reinforced gravel raft	The upper soils are excavated and removed and replaced with high strength structural fill (using quarry graded hardfill such as GAP65), often reinforced with multiple layers of geogrid, to form a structural raft to support building structures and floor slabs. The minimum thickness of the raft (which can be a combination of new hardfill associated with ground raising and below ground hardfill replacement) would need to be approximately 3 m for buildings. This option is unlikely to be cost effective for external pavements/yards.	Yes	No (only partially)	Provides a uniform and stiff bearing layer to support buildings on shallow foundations and slabs on grade. Simple operation that could be easily conducted as part of 'normal' earthworks operations.	Not a complete solution in isolation, i.e. the ground would also require treatment for settlement (e.g. by preloading). Requires significant volume of structural fill imported from off site and disposal of the excavated material – either on site or off site. Excavation below groundwater level may be problematic	Medium



Table 4-4: Ground Improvement Options (continued)

Ground improvement option	Details	Addresses risks from		Pros	Cons	Relative cost appraisal
		Liquefaction	Settlement			
Excavation and re-compaction – Ground Improved raft	An upper layer of natural ground (where the Taupo Pumice Alluvium is present) is excavated to a depth below design subgrade level and replaced successively in 300 mm thick layers. Heavy compaction (using a 10t roller with vibratory mode capability) is applied to each successive layer to achieve a high degree of compaction. Cement and lime could be added to the materials to improve overall strengths if needed. The improved "raft" of high strength ground is sufficiently dense so as to mitigate the liquefaction susceptibility risk under a ULS seismic event meaning buildings and pavements can be safely supported on grade. The minimum thickness of the raft (which could be a combination of new, compacted bulk fill associated with ground raising and compacted natural soils) would need to be approximately 3 m for buildings and approximately 1 m for pavements. The soils would most economically be stabilised by excavation to a maximum of 2.5 m below ground level. This would be completed by standard earthmoving plant together. The strength of the stabilised raft could be improved using layers of geogrid between layers .	Yes (upper 3 m)	No (only partially)	Provides a uniform and stiff bearing layer to support buildings on shallow foundations and slabs bearing on grade. Cost effective solution - works could be completed as a simple bulk earthworks operation. No need to import or export significant volumes of material to/from the site. The site is very large and has ample space for bulk earthworks operations (eg. laying out and conditioning of soils on site).	Not a complete solution in isolation, i.e. the untreated ground would also require treatment for settlement (e.g. by preloading). Excavation below groundwater level may be problematic, requiring installation of diversion/cut-off drains around the perimeter of the excavation. A stiff layer of soil would be required at the base of the excavation to support trafficking of earthmoving plant. Excavation depths may therefore be limited, or special treatment may be required at the excavation base (e.g. by the use of BIDIM geotextile and/or geogrid).	Low-medium
Dynamic Compaction (DC)	The upper 3 to 5 m is compacted by dropping a heavy weight (approx. 10t) with a diameter of 1 to 2 m from a height of 6 to 10 m using a large crawler crane. The weight is dropped several times in one location until the compaction effectiveness is reduced (the optimum number of drops is usually determined by a trial prior to commencing). Drop locations are usually spaced at 1.5 to 2 x D (D= diameter of the weight). The "pitted" surface requires re-levelling and surface compaction following completion	Yes (upper soils)	No (only partially)	Very effective in sandy and other granular soils such as those present at near surface levels at this site. Simple operation that has been widely used and tested in New Zealand. Effectiveness can be easily assessed by performing tests pre and post DC.	Only suitable in predominantly sandy soils. Is not suitable for areas directly underlain by clayey and peat soils (e.g. Rotokawau Formation). Will require significant filling following compaction to building levels back up to original (pre DC) site elevations.	Low



4.7.3 Ground Improvement Option Selection

With reference to the various options outlined in Table 4-4 above, the following key criteria were considered for the selection of a recommended ground improvement option for this site for consideration as part of the geotechnical assessment process;

- Mitigation of liquefaction susceptibility risk (providing a minimum 3 m thick raft of non-liquefiable soils below any future building platform and up to 1 m below future road and yard pavements and the rail siding)
- Minimisation of consolidation and secondary compression settlement to magnitudes that are considered tolerable to future buildings, floor slabs and other pavements subject to sustained loading (e.g. yard areas)
- Provides for a subgrade of sufficient strength and thickness for construction of new road pavements and car parks
- Cost effectiveness
- Performance and effectiveness/risk
- Availability of resources (preferably locally)

With respect to the above criteria, we recommend that one of the two following options be considered when assessing future development on this site:

1. Excavation and re-compaction to form a stabilised raft in combination with preloading, or
2. Dynamic compaction in combination with preloading

Excavation and re-compaction or dynamic compaction will address the surficial soils (upper 2 to 3 m) providing a minimum crust thickness of 3 m below future building platforms and at least 1 m below future pavements (yards, roads, rail sidings etc). Preloading is intended to address long term settlement issues and would be required over the majority of all future building platforms and in other areas of the site subject to sustained surface loading (e.g. yard areas). These options are discussed in more detail below.

In Situ Raft Stabilisation

Excavation and re-compaction to form a ground improved raft of upper soils would involve excavation of the existing silty SAND (Taupo Pumice Alluvium) to a depth of between 1.5 m and 2.5 m below present ground level, beneath future building footprints. The same material (excluding any peat and/or soft clay encountered over this depth range) would then be progressively re-compacted in 300-350 mm thick lifts (loose thickness). Lime and cement could be blended with each layer using a hoe to improve the strength of the soil.

To provide a minimum crust thickness of at least 3m below future building slabs, the balance of the raft (1.5 to 0.5 m) would need to be formed using engineered fill to lift the site above present ground levels. New fill would ideally be SPR (quarry overburden) or alternatively cohesive soils (clays/silts) that are not susceptible to liquefaction. The thickness of new fill above present ground level will vary depending on the design levels of the building platform versus present site levels and the maximum practical cut (constrained by groundwater levels and the presence of peat and/or very soft clays/silts that underlie the Taupo Pumice Alluvium). It is recommended that at least 600 mm of Taupo Pumice Alluvium be left in situ over the underlying very soft soils to provide a working platform for supporting earthworks plant. The upper 300 mm of this layer may be able to be stabilised in situ using heavy vibratory rolling. If there is an insufficient thickness of Taupo Pumice Alluvium left in situ, it may be necessary to import SPR and place a working layer of at least 400 mm thickness in the base of the excavation. This would be used to form a 'stiff' platform on which to place and compact subsequent layers of stabilised fill.

For external pavements areas (yards, heavy traffic zones, road carriageways and the rail siding, the depth of the stiff crust could be decreased to between 1 and 1.5 m. As with the building platforms, the

stiff crust can be made up of a combination of improved subgrade (excavated and recompacted) and/or new imported fill (preferably SPR).

The depth and thickness of the in-situ stabilisation and thickness of new, high strength fill will vary across the site and potentially across individual building platforms. This will need to be assessed on a case by case basis and will require further investigation.

The strength of the raft could be improved using layers of geogrid between compacted layers.

Groundwater levels beneath an area proposed to be in situ stabilised would need careful consideration to ensure the excavation and replacement is feasible and can be undertaken safely.

Dynamic Compaction

Dynamic Compaction (DC) could be considered as an alternative to in situ raft stabilisation for treating surface soils (upper 2-3 m). A preliminary dynamic compaction trial was undertaken (August 2019) on the site in an area underlain by 3-5m of Taupo Pumice alluvium. The method was confirmed to effectively mitigate the liquefaction susceptibility of these near surface sandy soils. As outlined in Table 4-4, Dynamic Compaction (DC) involves the repeated dropping of a heavy weight (8-12t) from a height of 6-10 m. The amount of energy (tonne.metres), and the number of drops required to compact the ground adequately will depend largely on the material type and thickness. The drop height, weight, number of drops and spacing of the drops will need to be determined by performing a trial on site in various different locations. However, for preliminary assessment purposes, we recommend allowing for the following:

- 8 to 12t weight, 1.5 to 2.0 m in diameter
- Drop height of 6 to 10 m
- Drop spacing of approx. 1.5 x weight diameter
- Min. 5 drops per location

Following completion of DC, the pitted surface will need to be re-levelled and recompacted to densify the disturbed soils around the drop locations. As the site level will be substantially lower following DC works, the platform will need to be lifted to design grade using imported fill (sourced either from on site or offsite). To ensure there is a min. 3 m thick raft beneath future building platforms, the imported fill layer may need to be at least 1 m thick.

Dynamic compaction should only be attempted in areas which are underlain by granular soils (e.g. Taupo Pumice Alluvium and Karapiro/Puketoka Formation sands). It is not usually an effective method for compaction of cohesive (clay/silt) soils or peats. The effectiveness of DC on soils below groundwater level is also somewhat limited as the pore water in the soil matrix cannot rapidly dissipate.

DC results in significant ground vibrations within 20 to 50 m of the works area. Whilst most of the works are likely to be sufficient well offset from neighbouring properties, vibration effects may need to be addressed for neighbouring properties located within 50 m of the site.

Preloading

Preloading is required to address medium to long term settlement issues associated with consolidation and secondary compression of soils extending to great depths (40 m or more below ground level). Of primary concern is the Rotokawau Formation soils (very soft silts/clays and peat) which are between 10 and 20 times more compressible than the other geological units present at the site (Puketoka Formation and Karapiro Formation). The Rotokawau Formation varies between less than 1 m and 13.5 m in thickness across the site and is thickest at the eastern end of Lot 1, DPS 29288.

Where the thick layers of organic soils/peat (Rotokawau Formation) are present at the eastern end of the site these can have large proportion of secondary 'creep' settlement which may continue to occur

for the design life of a structure and may be outside tolerable limits. This secondary settlement is very difficult to predict and often cannot be eliminated solely by the placement of preload and surcharging.

Preloading is likely to be required in the following areas:

- All building platforms that aren't load compensated (i.e. "unloaded" by cut earthworks) or positioned entirely over "high ground with an elevation of RL > 9 m" that is underlain directly by Karapiro/Puketoka Formation soils;
- All yard areas which could be subjected to medium to long term loading and the rail siding.
- Roads and rail siding where fill is being placed to lift the design levels

The required preload height will depend on the nature of the development (i.e. light industrial versus commercial/retail buildings), however, for preliminary purposes we recommend allowance for the following:

- A 35 kPa surcharge pressure which could be formed using Soft Pit Run, 2.0 m high (unit weight of 17-18 kN/m³ with nominal compaction) or a site sourced material (e.g. Taupo Pumice Alluvium) to a height of 2.2 -2.3 m (unit weight of 15-16 kN/m³ with nominal compaction).
- The preload should extend over the entire building footprint plus an additional width of 5 m around all boundaries.
- Installation of preload monitoring instrumentation including profilometers, piezometers, extensometers and survey pins with regular monitoring;
- A hold period of approximately 12-18 months (to be confirmed) to allow for up to 90% of theoretical maximum consolidation to occur. This preload period can be reduced by either surcharging (placing additional fill on top of the preload) or by installation of "wick drains". Given the relatively sandy nature of the subsoil materials above and below the Rotokawau Formation, the use of "wick drains" is unlikely to provide much benefit.

Actual preload details and timeframes would be the subject of a detailed preload design. Following completion of the consolidation period, the preload material can be removed and either used directly as bulk fill material or as a preload for additional, future building platforms.

It is recommended that a trial preload be undertaken in at least two locations at the site, as early as possible prior to commencing any future building developments. Information from trial preloads can be used to rationalise preload design (optimising preload heights and extents), to determine the likely magnitude of settlements (to assess over-fill heights) and post-construction settlements (so that these can be accommodated in building design). A trial preload would also be used to determine timeframes for completion of the consolidation period. Preload instrumentation, such as profilometers, piezometers and extensometers installed beneath a trial preload, could be used to enable back-calculation of soil parameters (the compressibility and permeability of the various soil units) which could then be used to engineer 'production' preloads.

4.8 Building Foundations and Floor Slabs

Provided that the building platforms are subject to the ground improvement works to mitigate liquefaction and/or settlement risks, as outlined in Section 4.7 below, future building structures and floor slabs could be fully supported on grade, i.e. shallow pad footings for support of portal frame structures and strip footings to support perimeter precast panel walls.

As outlined in Section 4.4, it is essential that a minimum "crust thickness" (non-liquefiable soils) of at least 2.5 m is present below the underside of all shallow foundations to eliminate the life-safety threat from liquefaction during a ULS seismic event.

Piled foundation options could be considered as an alternative for support of building structures. However, as there is no continuous and reliable end-bearing strata to bear on to, piles would need to rely on skin friction resistance only and may need to extend to considerable depths to achieve suitable load capacities. As the potential for liquefaction in sandy layers of the Karapiro and Puketoka

Formation is high (ULS seismic case) a significant component of negative skin friction would need to be considered for design. The load contribution from post-seismic downdrag effects is likely to make deep pile foundations highly inefficient for support of building structures. Furthermore, supporting building structures on piled foundations and floor slabs on grade may result in the floor slab “hanging-up” on pile caps with sag deformation of the slab between pile locations.



5. Further Work

As noted throughout this document, further geotechnical investigations and detailed geotechnical analysis will be required to support the subdivision and consenting stage of any future development.

The scope of additional geotechnical investigations is likely to include the following;

- Fully cored machine boreholes extending to depths of approximately 30 m below ground level with regular sampling for laboratory testing;
- Installation of groundwater monitoring instrumentation (piezometers) for measuring groundwater levels and assessing seasonal groundwater fluctuations;
- Infill Cone Penetration Tests (CPTs) to achieve a regular, typical spacing of approximately 50m between each test in future development areas;
- Test pits extending to depths of approximately 3 m below ground level for categorisation/characterisation of near surface soils, and for bulk sampling and laboratory testing;
- A suite of laboratory testing to characterise soils for earthworks design, confirm liquefaction susceptibility, and assess soil compressibility characteristics.

The above investigations would likely be completed in stages as the development is progressed.

Following completion of investigations, the following geotechnical appraisal and analysis work will be required;

- Additional settlement and liquefaction analyses;
- Assessment of the suitability of site won material for re-use as engineered fill and derivation of compaction criteria for earthworks specifications;
- Confirmation of the proposed ground improvement option;
- Design of a trial preload, or alternatively a production preload for a future building platform;
- Assessment of post-construction settlements, following preloading, to confirm that these can be tolerated by the building structures, floor slabs and pavements;
- Assessment of subgrade strengths for pavement design.

6. Conclusions

A preliminary geotechnical investigation has been undertaken as part of a geotechnical assessment of the site located between Tahuna Road and Balemi Road, Ohinewai. The objective of the investigation was to assess the suitability of the site for mixed use development ranging between light industrial, warehouse/factory buildings to residential dwellings.

The conclusions and preliminary geotechnical advice presented in this report are intended to support a feasibility assessment for development of the land. Further geotechnical investigations and detailed geotechnical analyses will be required for design.

Ground Conditions

1. The site is underlain by Tauranga Group soils comprising a surface layer of Taupo Pumice Alluvium (1-3 m thick) over Rotokawau Formation soils (1 to 13.5 m thick) and Karapiro/Puketoka Formation extending to depths of around 40 m below ground level. The Whangamarino Formation occurs below the Karapiro/Puketoka Formation unit and is underlain by Te Kuiti Group “bedrock” at approximately 100 m depth.
2. The Rotokawau Formation is a recent alluvial deposit comprised of very soft soils (clays/silts and peat) with typical undrained shear strengths of 5 to 10 kPa. This material is highly compressible.
3. The Karapiro/Puketoka Formation soils are Pleistocene Age deposits comprising interbedded sands, silts, clays and peat with some gravel beds. These soils are considerably less compressible than the Rotokawau Formation but are still expected to settle under surcharge pressures.
4. The lower lying areas of the site (RL 7.5 m and below) are generally characterised by greater thicknesses of the Rotokawau Formation and are therefore considerably more challenging, from a geotechnical perspective, to develop. By contrast, areas of the site with surface elevations greater than RL 9.0 m are typically directly underlain by Karapiro/Puketoka Formation soils that are of higher strength and less compressible.
5. There are several areas of the site which are considered to be significantly constrained for future development. These are delineated as areas of potential ‘large magnitude’ settlement (hatched red on Figure 529-004 in Appendix A).
6. Groundwater is expected at near surface levels (0.5 to 1.5 m below ground level).

Earthworks

7. The Taupo Pumice Alluvium (silty, pumiceous sand) and the Karapiro/Puketoka Formation soils are expected to be largely suitable for re-use as engineered fill. Some conditioning and blending may be required to achieve suitable compaction specifications.
8. Excavation below groundwater level should be avoided wherever possible as groundwater inflows are likely to be significant and could result in “running sands” and instability of soft clays/silts and peat.
9. The Rotokawau Formation soils are very unlikely to be suitable for use as engineered fill;
10. Wherever possible, a minimum “working cover” of approximately 800 mm should be maintained above the surface of the very soft Rotokawau Formation soils. Alternatively, a layer of SPR may need to be placed over the top of the soft soils to provide a working platform upon which fill can be compacted over.
11. Placement of fill above existing ground level is likely to initiate ground surface settlement which will need to be considered for design and construction of civil infrastructure and buildings. A sufficient lag time should be allowed between completion of fill and construction of civil infrastructure and new buildings.
12. Where “high ground” areas of the site are cut down, these areas will be partially to fully load compensated. This will mitigate or eliminate the settlement potential from future building loads.



13. Allowance should be made for undercut and removal of significant volumes of unsuitable soil and for importation of quality bulk fill (e.g. soft put run/quarry overburden) or cohesive soils (clays/silts)

Site Seismicity and Liquefaction

14. Where more than 10 m of very soft soils with an undrained shear strength of less than 12.5 kPa (Rotokawau Formation) is present, the site should be categorised as Class E – soft soil site for seismic design purposes. Elsewhere, the site could be considered Class D, however there is presently insufficient investigation data to accurately delineate these areas.
15. Preliminary liquefaction analyses were undertaken using CPT test results to assess the liquefaction susceptibility of the subsoils under both SLS (50-year AEP) and ULS (500-year AEP) seismic events. The results indicate that there is a low risk of liquefaction occurring under SLS conditions. However, under ULS shaking (PGA = 0.22g), the subsoils are considered to be liquefiable from near surface (below groundwater level).
16. The potential effects of liquefaction are potentially “severe” over parts of the site (liquefaction severity number, LSN > 50) with potential for large magnitude total and differential settlements affecting structures, and damaging services. The variability of potential liquefaction effects across the site is presented on Figure 529-003 in Appendix A.
17. Liquefaction of the near surface soils (Taupo Pumice Alluvium) may present a “life-safety” risk for buildings supported on shallow foundations embedded within or over this layer.
18. Ground improvements will be required to mitigate the effects of liquefaction at this site.

Settlement

19. Settlement is expected to occur across most of the site where new stresses are introduced to the ground (e.g. placement of new fill, building floor slab dead loads and live loads, foundation bearing pressures etc). Figure 529-004 presents the range of settlements anticipated across the site for a uniform surface loading of 45 kPa (1 m of bulk fill, slab dead weight of 10 kPa and a distributed floor slab live load of 15 kPa).
20. Total estimated settlements for a 45 kPa surcharge pressure generally range between 100 mm to > 2,000 mm with the magnitude of settlement proportional to the thickness of the Rotokawau Formation soils. These materials are between 10 and 20 times more compressible than the Karapiro/Puketoka Formation soils.
21. Preloading of most building platforms, yard areas, the rail siding and possibly some road corridors is recommended to mitigate the risk of post-construction settlements affecting buildings and pavements.
22. Even following preloading, ongoing secondary compression (creep) settlement may still occur over the design life of the structures. The magnitude of post construction settlement will need to be carefully evaluated to confirm that the future ground movement can be accommodated by building structures and infrastructure.
23. Areas of “high ground” (RL > 9 m) which are cut down to form gently graded land or terraced platforms for buildings will be partially or wholly load compensated for future building loads. These areas would therefore not require preloading.

Civil Infrastructure

24. Installation of buried services below groundwater level is likely to be problematic due to the presence of high groundwater levels in combination with loose sands at near surface levels. Trenches are unlikely to maintain any stability. It is therefore recommended that trenchless installation methods be considered (e.g. thrusting) for service installation, or that service trenches are maintained above groundwater level (in new fill and natural soils).
25. The ground beneath future road pavements, yards and the rail siding should be improved to a depth of between 1.0 and 1.5 m below ground level to provide a stiff raft for support of the

pavements, for effective load spreading and to mitigate the effects liquefaction during a ULS seismic event.

26. Yard areas and the future rail siding should also be preloaded to minimise the risk of long-term settlement effects.

Ground Improvements

27. Various different ground improvement options have been presented in Table 4-4 of this report. These are intended to minimise post-construction settlements, to provide a stiff raft for future buildings and pavements to bear on and to mitigate the effects of liquefaction following a ULS seismic event. Pros and cons of each option, along with a qualitative assessment of costings are also presented in the table.
28. Two different ground improvement options have been identified as being potentially well-suited to this site;
 - a. Excavation and re-compaction of upper soils (sands only) in combination with Preloading; and
 - b. Dynamic Compaction in combination with preloading. The pros and cons of these two options, along with concept design details are presented in Section 4.7.3.
29. Field trials have been undertaken to confirm the viability of Dynamic Compaction and results demonstrate the feasibility of this method. A preload trial is also recommended to determine required preload heights, extents, timeframes and post-construction settlement magnitudes.
30. Vibration effects from Dynamic Compaction will need to be considered for any properties within 50 m of the works area.

Building Foundations

31. Provided that future building platforms have been subject to ground improvement that effectively mitigates the risk of liquefaction in the upper soils and settlement, it is expected that most structures could be supported on shallow foundations with a slab bearing on grade. Settlement tolerant structures and cladding systems are recommended. Floor slabs should be post-tensioned or fibre reinforced or otherwise designed to tolerate some differential settlement.

Further work

32. Additional geotechnical investigations and geotechnical analyses will be required to support design and detailing of the subdivision earthworks, civil infrastructure and all new buildings. A provisional scope of further investigation and analysis is outlined in Section 5. This will need to be confirmed as development details and plans are finalised.

7. Applicability

This report has been prepared for our client, Ambury Properties with respect to the brief provided to us. The advice and recommendations presented in this report should not be applied to any other project or used in any other context without prior written approval from Initia Limited.

Report prepared by:



Nick Speight
Senior Geotechnical Engineer

Report reviewed by:



Matthew Wansbone
Senior Geotechnical Engineer

Document control record


Report Title		Proposed Plan Change, 231 Tahuna Road, Ohinewai Geotechnical Assessment Report			
Initial Project Reference		P-000529			
Client		AMBURY PROPERTIES			
Revision	Date	Revision detail	Author	Reviewer	Approved by
A	31/10/19	Draft Issue for Comment	M. Wansbone	N. Speight	M. Wansbone
Current Revision		A			



Appendix A: Figures








0 75 150 225 300 375 SCALE 1 : 7,500m					FOR INFORMATION				
NOT FOR CONSTRUCTION THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED					AMBURY PROPERTIES				
APPROVED:					PROPOSED MIXED USE COMMERCIAL AND LIGHT INDUSTRIAL DEVELOPMENT				
DATE:					GEOTECHNICAL INVESTIGATION TEST LOCATION PLAN AT 231 TAHUNA ROAD, OHINEWAI				
Rev					Initial Project ref: P000529				
Revision Description					Figure Number 529-001				
Designed					Revision B				
Drawn									
Checked									
Scale									
AS SHOWN									
Original Size									
A3									

NOT FOR CONSTRUCTION THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED				
APPROVED:				
DATE:				
Rev				
Revision Description				
Designed				
Drawn				
Checked				
Scale				
AS SHOWN				
Original Size				
A3				



Unit 13, 114 St Georges Bay Rd
Parnell, Auckland, 1052
Phone: +64 9 977 0462
Email: enquiries@initia.co.nz



LEGEND

TAURANGA GROUP
HOLOCENE AGE RIVER DEPOSITS
(SAND, SILT, MUD AND CLAY WITH
LOCAL GRAVEL AND PEAT BEDS)

TAURANGA GROUP
PLEISTOCENE AGE
PUMICEOUS RIVER DEPOSITS
(COURSE PUMICEOUS AND RHYOLITIC SANDS
AND CURRENT - BEDDED GRITS, WITH
INTERBEDDED PEAT AND LOCAL GRAVELS)

APPROXIMATE SITE BOUNDARY

NOTES:
GEOLOGICAL BOUNDARIES AND DESCRIPTION SOURCED
FROM GNS SCIENCE NZ GEOLOGY WEB MAP 1 : 250,000

075150225300375

SCALE 1 : 7,500m

FOR INFORMATION

				NOT FOR CONSTRUCTION <small>THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED</small>		<div><div></div><div>INITIA</div><div>GEOTECHNICAL SPECIALISTS</div></div>	Unit 13, 114 St Georges Bay Rd Pamell, Auckland, 1052 Phone: +64 9 977 0462 Email: enquiries@initia.co.nz	AMBURY PROPERTIES	PROPOSED MIXED USE COMMERCIAL & LIGHT INDUSTRIAL DEVELOPMENT	
				GEOLOGICAL MAP					Initia Project ref: P000529	
									Figure Number 529-002	
									Revision B	
B Lots 2 & 3 DP474347 Added		AW	GA	AW						
A First Issue		NS	LN	NS	DATE:					
Rev	Revision Description	Design	Drawn	Checked	Scale	AS SHOWN	Original Size	A3		

© Document copyright of Initia Ltd 2018 and may only be used for its intended purpose.

G:\PROJECTS\INITIA\PROJECTS\P000529 OHENWA29-G-002.DWG Document No.



075150225300375

SCALE 1 : 7,500m

FOR INFORMATION

<div>NOT FOR CONSTRUCTION</div> <div>THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED</div> <div>APPROVED:</div>				<div><div>INITIA</div><div>GEOTECHNICAL SPECIALISTS</div></div>	<div>Unit 13, 114 St Georges Bay Rd Pamell, Auckland, 1052</div> <div>Phone: +64 9 977 0462 Email: enquiries@initia.co.nz</div>	<div>AMBURY PROPERTIES</div>	PROPOSED MIXED USE COMMERCIAL & LIGHT INDUSTRIAL DEVELOPMENT	
LIQUEFACTION SEVERITY FOR ULS EARTHQUAKE (PGA = 0.22g MW = 5.8)		Initia Project ref: P000529						
		Figure Number 529-003						
		Revision B						

Rev

Revision Description

Design

Drawn

Checked

Scale

AS SHOWN

Original Size

A3

B

LOTS 2 & 3 DP 474347 ADDED

AW

GA

AW

A

First Issue

LN

LN

NS

DATE:

©

Document copyright of Initia Ltd 2018 and may only be used for its intended purpose.

Document No.

529-003

C:\PROJECTS\INITIA\PROJECTS\P000529_OHNIWA529-G-003.DWG



LEGEND

ESTIMATED TOTAL SETTLEMENT ZONES
(45 KPa SURCHARGE)

	< 100mm
	101 - 200mm
	201 - 500mm
	> 500mm

CPT12 925 ESTIMATED SETTLEMENT (mm) AT CPT LOCATION

APPROXIMATE SITE BOUNDARY

075150225300375

SCALE 1 : 7,500m

FOR INFORMATION

<div>NOT FOR CONSTRUCTION</div> <div>THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED</div> <div>APPROVED:</div>				<div></div> <div>GEOTECHNICAL SPECIALISTS</div>	<div>Unit 13, 114 St Georges Bay Rd Pamell, Auckland, 1052</div> <div>Phone: +64 9 977 0462 Email: enquiries@initia.co.nz</div>	<div>AMBURY PROPERTIES</div>	PROPOSED MIXED USE COMMERCIAL & LIGHT INDUSTRIAL DEVELOPMENT	
SETTLEMENT ZONING PLAN 45 KPa SURCHARGE		Initia Project ref: P000529	Revision: B					
		Figure Number: 529-004						
B	LOTS 2 & 3 DP 474347 ADDED	AW	GA	AW				
A	First Issue	LN	LN	NS	DATE:			
Rev	Revision Description	Designed	Drawn	Checked	Scale	AS SHOWN	Original Size A3	

© Document copyright of Initia Ltd 2018 and may only be used for its intended purpose.

G:\PROJECTS\INITIA\PROJECTS\P000529_OHNEWAS29-G-003_AND_004.DWG

Document No.

Appendix B: Geotechnical Factual Report





INITIA

GEOTECHNICAL SPECIALISTS

AMBURY PROPERTIES

231 TAHUNA ROAD, OHINEWAI

GEOTECHNICAL FACTUAL INVESTIGATION
REPORT

INITIA REF P-000529 REV 2

OCTOBER 2019

Table of Contents

1.1	Introduction.....	3
1.2	Site Description	3
1.2.1	Location.....	3
1.2.2	Description	3
1.3	Development Proposal.....	4
1.4	Site Investigations	4
1.4.1	General	4
1.4.2	Historical Geotechnical Investigations.....	4
1.4.3	Recent Investigations	5
1.4.3.1	Stage 1 Investigations.....	5
1.4.3.2	Stage 2 Investigations.....	7
1.4.3.3	Stage 3 Investigations.....	8
1.5	Applicability	9
Appendix A:	GFR-Geotechnical Investigation Plan	
Appendix B:	GFR-Machine Borehole Logs and Photos.....	
Appendix C:	GFR-Cone Penetrometer Test Logs.....	
Appendix D:	GFR-Test Pit Investigation Logs.....	
Appendix E:	GFR-Laboratory Testing Results	
Appendix F:	GFR-Historical Investigation Data	
	 Figure 1: Site location and legal boundaries	3
	 Table 1: Summary of machine borehole investigations.....	5
	Table 2: Summary of Cone Penetration Test investigations	6
	Table 3: Summary of test pit investigations.....	7
	Table 4: Laboratory testing schedule	8
	Table 5: CPT testing summary	9



1.1 Introduction

This factual report presents the results of a preliminary geotechnical investigation and laboratory testing undertaken across the site located at 231 Tahuna Road, Ohinewai, Waikato. The purpose of the geotechnical investigation was to assess the ground conditions and evaluate geotechnical constraints and opportunities for a proposed mixed-use development.

The geotechnical investigations are preliminary only and if development on this site was to occur, detailed geotechnical investigations will be required to support design and consenting stages of the project.

This report is a factual summary of the site and geotechnical investigations and laboratory testing only. Interpretation of the geotechnical data and preliminary geotechnical advice on the development potential of the land will be presented in a separate report.

1.2 Site Description

1.2.1 Location

The site encompasses five legal properties located on the eastern side of State Highway 1, at 231 Tahuna Road and Balemi Road, Ohinewai. The total site area is approximately 178 ha and is made up of the properties legally described as Allotment 405, Whangamarino Parish (~37 ha), Lot 2, DP 474347 (~0.8 ha), Lot 3, DP 474374 (~10.9 ha), Lot 1, DPS 29288 (~68 ha) and Lot 2, DP 29288 (~61 ha). The location of the site and the individual property boundaries are presented in Figure 1 below.




Figure 1: Site location and legal boundaries

1.2.2 Description

The site is presently almost completely grass covered and is used for agricultural purposes. It is bounded by Tahuna Road to the south, Balemi Road and other agricultural land to the north, Department of Conservation land (including Lake Rotokawau) to the east, and Lumsden Road to the west.

The land is typically low lying and flat with the exception of a low ridgeline on the southern boundary (which Tahuna Road has been formed on) and two spurs which run in a north south direction through the two southern properties (Lots 1 and 2, DP 29288). With reference to Figure 529-01 attached in Appendix A, ground surface elevations vary between approximately RL 20 m on the southern boundary with Tahuna Road and RL 6 m at the far eastern end of the site. With the exception of the localised ridge lines, the general site grade falls very gently from west to east.

The Waikato River is located approximately 1 km to the west of the site.

1.3 Development Proposal

The Illustrative Masterplan for the development (Adapt Studio, Revision J) shows that the proposed development could include the following;

- A single use development over the 37 ha property at the north of the site, including a 5 to 10 ha warehouse/factory with surrounding yards and carparking;
- A rail connection from the main trunk line (west of the site) along the northern boundary of Allotment 405 (37 ha property);
- Light industrial development over Lot 3 DP 474374 – the 10.9 ha property at the western side of the site;
- Mixed light industrial and retail development, with possible residential development at the eastern end of Lot 2 DPS 29288 – the 61ha property at the south western end of the site;
- Residential and community facilities over Lot 1 DPS 29288 – the 68 ha property – at the south eastern end of the site;
- Internal roads and installation of civil services;
- Parks and reserve land.

1.4 Site Investigations

1.4.1 General

Geotechnical investigations were carried out at the site in three stages. The first stage of the investigation was completed between 5 September and 14 September 2018, the second stage on 31 October 2018 and the third stage on 29 July 2019. The Stage 1 investigations comprised a limited number of machine boreholes and Cone Penetration tests (CPTs). Test pits were completed for the Stage 2 investigations to collect soil samples for laboratory testing. The Stage 3 investigations were completed following provision of access to Lot 2 and 3 DP 474374. Investigation locations were selected by Initia to provide an overview of the ground conditions across the entire site (tests spaced at approximately 250 m centres). Co-ordinates were extracted from AutoCAD for the proposed test locations and were set out on site using a hand-held GPS unit.

Several of the proposed investigations (CPTs) at the eastern end of the site could not be undertaken due to the saturated nature of the ground at the time of the fieldwork.

A geotechnical investigation location plan is presented on Figure 529-01 in Appendix A. Investigation locations should be considered approximate only (+/- 10 m from actual locations)

1.4.2 Historical Geotechnical Investigations

As part of a desk study assessment of the site, Initia has located a series of reports which document the results of an extensive geotechnical investigation undertaken in Ohinewai in the early 1980's for a proposed opencast coal mine. As part of this investigation, several deep machine boreholes were drilled over multiple investigation phases within the site boundaries (specifically within Lot 1, DP 29288) and to the south and south east of the site. The locations of all known investigations undertaken for the Ohinewai open-cast coal mine feasibility study are presented on Figure 529-01 attached in Appendix A. Data from the Phase 2 geotechnical investigation¹ has only been able to be sourced. Copies of the relevant machine borehole logs (BH 9782, BH9783, BH9796, BH9797 and

¹ State Coal Mines: Ministry of Energy; Ohinewai Opencast Feasibility Study; Geotechnical Investigations Phase II, December 1986, Volume 1 and Volume 2, prepared by RWL Mining Consultants

BH9842)² are attached in Appendix F of this report. Other borehole logs are available within the Phase 2 investigation report however, these were wash-drilled to a depth of approximately 60 m and are therefore of little value for the purposes of this assessment.

1.4.3 Recent Investigations

1.4.3.1 Stage 1 Investigations

Machine Boreholes

The drilling of three cored machine boreholes (at two locations) was undertaken over the period 6 to 10 September, 2018. Borehole 1 (BH1) was drilled to a depth of 17 m using a tractor mounted, rotary coring drilling rig, supplied and operated by DCN Drilling Ltd. In situ strength testing, comprising shear vane tests (in cohesive soils) and standard penetration tests (in sands) were performed at 1.5 m depth intervals. A combination of open-barrel and HQ3 triple tube coring was undertaken throughout this borehole, however, due to the soft/loose nature of the soils, core recovery was limited and the borehole was abandoned above the target depth of 25 m.

A sonic rig was used to re-drill borehole BH1 (BH01a) to achieve better core recovery. In situ testing (SPTs) was commenced from the termination depth of borehole BH1 (17 m depth) and borehole BH01a was terminated at the target depth of 24.5 m.

Borehole BH2 was also drilled using the Sonic rig and achieved relatively successful core recovery. As with BH01/BH01a, in situ strength testing (shear vanes and SPTs) were carried out at 1.5 m depth intervals. BH02 was terminated at a depth of 21 m below ground level.

All drilling works were carried out under the full-time supervision of a senior field geologist from Geotechnics Ltd. The recovered drill core was logged in accordance with the New Zealand Geotechnical Society "Field Description of Soil and Rock" Guidelines.

Investigation locations are presented on Figure 529-01 in Appendix GFR-A. Machine borehole logs and core photographs are presented in Appendix GFR-B. A summary of the machine borehole details is presented in Table 1 below.

Table 1: Summary of machine borehole investigations

Investigation ID	Easting (mE, NZTM2000)	Northing (mN, NZTM2000)	Elevation (m, RL) ¹ .	Termination depth (m, b.g.l)
BH1	1791070	5849472	10.5	16.95 m
BH1a	1791070	5849471	10.5	24.45 m
BH2	1791894	5849542	6.5	21.0 m

Note 1: The ground surface elevations presented are based on interpretation from Waikato Regional Council LIDAR and are expected to be accurate to + or - 1m.

Cone Penetration Tests

A total of 48 No. Cone Penetration Tests (CPTs) were carried out by Geotech Drilling Ltd between 5 and 14 September 2018. A further 9 CPTs were proposed but were deleted (CPT's 36, 39, 41, 45, 46, 49, 50, 51, 52) due to site access issues associated with the saturated, soft ground at the time of investigation.

² New Zealand State Coal Mines: Ohinewai Underground Prospect; Geotechnical Testing of Core Samples from Boreholes 9802, 9803, 9084 and 9805, prepared by Central Laboratories, Report 2-85/19 Vol1 and Vol 2



The CPTs were extended either to the target depth of 25 m below ground level or until 'refusal' occurred (from a combination of cone resistance and skin friction) or from failure of the reaction anchors which were embedded in the upper, soft soils.

The CPT investigation locations are presented on Figure 529-01 in Appendix GFR-A. CPT traces (qc, fs, friction ratio and pore water pressure profiles only) are attached in Appendix C. A summary of the CPT tests is presented in Table 2 below.

Table 2: Summary of Cone Penetration Test investigations

CPT Ref	Easting (mE, NZTM2000)	Northing (mN, NZTM2000)	Elevation (m, RL) ¹	Termination depth (m, b.g.l)	Comment
1	1791057	5849650	8.0	4.5	Refusal on dense sand
2	1791263	5849667	8.0	25	Target depth
3	1791469	5849685	8.0	25	Target depth
4	1791675	5849702	8.0	25	Target depth
5	1791881	5849720	7.5	25	Target depth
6	1791070	5849472	10.5	25	Target depth
7	1791276	5849489	8.0	25	Target depth
8	1791482	5849507	7.5	25	Target depth
9	1791688	5849524	7.5	25	Target depth
10	1791894	5849543	6.5	25	Target depth
11	1791144	5849257	8.5	20.5	Refusal on dense sand
12	1791285	5849268	8.5	25	Target depth
13	1791491	5849286	8.5	25	Target depth
14	1791697	5849303	7.5	25	Target depth
15	1791903	5849321	7.0	20.3	Refusal on dense sand
16	1792148	5849283	8.0	14.4	Reaction anchor failure
17	1791504	5849091	7.0	17.1	Reaction anchor failure
18	1791706	5849100	7.5	17.7	Refusal on dense sand
19	1791949	5849123	7.0	11.5	Reaction anchor failure
20	1792152	5849131	14.5	22.8	Reaction anchor failure
21	1791361	5848993	7.5	17.5	Reaction anchor failure
22	1791524	5848874	8.5	13.5	Refusal on dense sand
23	1791718	5848900	6.5	15.8	Reaction anchor failure
24	1791945	5848937	6.0	18.6	Reaction anchor failure
25	1792160	5848958	7.5	11.8	Reaction anchor failure
26	1791360	5848786	8.0	12.5	Refusal on dense sand
27	1791728	5848708	11.0	6.0	Refusal on dense sand
28	1791955	5848734	6.0	17.0	Reaction anchor failure
29	1792169	5848782	7.0	11.4	Reaction anchor failure
30	1791329	5848628	13.0	6.5	Refusal on dense sand
31	1791546	5848606	16.5	16.5	Refusal on dense sand
32	1791741	5848554	19.5	25	Target depth
33	1791960	5848516	13.0	9.4	Refusal on dense sand



CPT Ref	Easting (mE, NZTM2000)	Northing (mN, NZTM2000)	Elevation (m, RL) ¹	Termination depth (m, b.g.l)	Comment
34	1792174	5848591	13.0	19.5	Reaction anchor failure
35	1792344	5849319	6.0	25	Target depth
37	1792760	5849319	6.5	25	Target depth
38	1792947	5849244	6.0	25	Target depth
40	1792350	5849131	6.0	14.0	Reaction anchor failure
42	1792777	5849040	6.5	25	Target depth
43	1792955	5849025	6.5	21	Reaction anchor failure
44	1793096	5848889	6.0	20	Reaction anchor failure
47	1792566	5848911	7.5	10.7	Reaction anchor failure
48	1792364	5848897	6.0	11.3	Reaction anchor failure
53	1793193	5848643	14.0	13.3	Reaction anchor failure
54	1792978	5848636	11.5	12.3	Reaction anchor failure
55	1792791	5848643	16.0	12.7	Reaction anchor failure
56	1792587	5848705	7.0	13.2	Reaction anchor failure
57	1792377	5848684	9.5	11.5	Reaction anchor failure

Note 1: The ground surface elevations presented are based on interpretation from Waikato Regional Council Lidar and are expected to be accurate to + or – 1m.

1.4.3.2 Stage 2 Investigations

Test Pits

Six machine excavated test pits were undertaken on 31 October 2018 using a 12t excavator operated by Broughton Contracting Ltd. The test pits were undertaken to sample the natural soils for lime / cement binder laboratory testing. Bulk samples (20 kg) bags were recovered from each of the test pits and transported to the Stevenson's Laboratory for testing. Sampling was carried out on the spoil stockpile from each test pit using the hand sampling method.

All works were carried out under the full-time supervision of a senior field specialist from Initia Ltd. The recovered test pit spoil was logged in accordance with the New Zealand Geotechnical Society "Field Description of Soil and Rock" Guidelines.

Investigation locations are presented on Figure 529-01 in Appendix GFR-A. Test pit logs and photographs are presented in Appendix GFR-D. A summary of the test pit investigations is presented in Table 3 below.

Table 3: Summary of test pit investigations

Investigation ID	Easting (mE, NZTM2000)	Northing (mN, NZTM2000)	Elevation (m, RL) ¹	Termination depth (m, b.g.l)
TP01	1791142	5849410	10	2.0
TP02	1791213	5849592	10	2.5
TP03	1791454	5849618	8.0	3.2
TP04	1791765	1791765	8.0	2.7
TP05	1791696	1791696	8.0	2.8
TP06	1791467	1791467	8.0	2.5

Note 1: The ground surface elevations presented are based on interpretation from Waikato Regional Council LIDAR and are expected to be accurate to + or – 1m.



Laboratory Testing

Samples taken from the test pits on the 31 October 2018 were tested by Stevenson's Laboratory who are an IANZ accredited civil materials testing laboratory. Testing included blending 1% lime and between 3 to 5% cement (proportion by dry mass of the soil) with the samples and allowing a 7-day curing time. Soaked Californian Bearing Ratio (CBR) tests were then performed on the cured samples. Particle Size Distribution (PSD) tests were also performed on representative samples from the test pits.

A summary of the laboratory testing completed with location references is outlined in Table 4 below. The results of the laboratory testing are presented in Appendix GFR-E.

Table 4: Laboratory testing schedule

Sample Ref #	Location	Depth (m)	Material	Quantity Soaked CBR%	Quantity Soaked CBR% + Binder			No. PSD
				Natural	1% Lime + 3% Cement	1% Lime + 4% Cement	1% Lime + 5% Cement	
1	TP01	0.5-1.0	SAND yellow brown with orange bands	1	1	1	1	1
2	TP01	1.3-1.6	SAND with pumice gravels		1	1	1	1
3	TP02	2.0-2.5	SAND with pumice gravels	1	1	1	1	1
4	TP03	1.3-1.6	SAND - grey wet		1	1	1	1
5	TP03	3.1	SAND with some silt grey light brown		1	1	1	1
6	TP05	0.5-0.8	SAND yellow brown with orange bands		1	1	1	1
7	TP05	2.5-2.8	SAND, grey	1	1	1	1	1

1.4.3.3 Stage 3 Investigations

Cone Penetrometer Testing (CPT) comprising 8 no. test locations was undertaken on 29 July 2019 within Lot 2 and 3 DP 474374. This testing was completed by Geotech Drilling Limited using a track mounted CPT rig which utilises screw in hold down anchors. These CPTs were advanced to their target depth of 20 m below ground level or 'refusal' (as a result of the failure of the reaction anchors which were embedded in the upper, soft soils; or effective refusal on a dense sand/gravel layer).

These ground investigation works were set out and managed by an Initia geotechnical engineer. The completed test elevations were surveyed with precise survey by SurveyWorx.

Investigation locations are presented on Figure 529-01 in Appendix GFR-A CPT traces (qc, fs, friction ratio and pore water pressure profiles only) are attached in Appendix C. A summary of the CPT testing completed is presented in Table 5 below.

Table 5: CPT testing summary

CPT Ref	Easting (mE, NZTM2000)	Northing (mN, NZTM2000)	Ground surface elevation (m, RL) ¹	Termination depth (m, b.g.l)	Comment
122A	1791581	5849251	7.0	20.0	Target depth
123	1791461	5849175	7.6	16.5	Refusal on dense sand
124	1791338	5849195	10.4	14.0	Reaction anchor failure
125	1791360	5849079	7.7	16.6	Refusal on dense sand
126	1791239	5849248	7.5	19.0	Refusal on dense sand
127	1791213	5849014	8.1	17.0	Refusal on dense sand
128	1791286	5848910	9.1	19.8	Target depth
129	1791284	5848790	8.4	12.5	Reaction anchor failure

Note 1: The ground surface elevations presented are from precise survey completed by SurveyWorx and are expected to have an accuracy of +/- 0.1m.

1.5 Applicability

This report has been prepared for our client, Ambury Properties, with respect to the brief provided to us. The advice and recommendations presented in this report should not be applied to any other project or used in any other context without prior written approval from Initia Limited.

Report prepared by:



Andy Wakelin
Senior Geotechnical Engineer

Report reviewed by:



Nick Speight
Senior Geotechnical Engineer
Director


Document control record

Report Title		231 Tahuna Road, Ohinewai Geotechnical Factual Investigation Report			
Initia Project Reference		P-000529			
Client		Ambury Properties			
Revision	Date	Revision detail	Author	Reviewer	Approved by
1	Oct 18	First Issue	M. Wansbone	N. Speight	M. Wansbone
2	Oct 19	Updated for 12.8ha block	A. Wakelin	N. Speight	N. Speight
Current Revision		2			



Appendix A: GFR-Geotechnical Investigation Plan





0 75 150 225 300 375					SCALE 1 : 7,500m					FOR INFORMATION				
					NOT FOR CONSTRUCTION					AMBURY PROPERTIES				
					THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED					PROPOSED MIXED USE COMMERCIAL AND LIGHT INDUSTRIAL DEVELOPMENT				
					APPROVED:					Geotechnical Investigation				
					DATE:					TEST LOCATION PLAN				
					Rev					AT 231 TAHUNA ROAD, OHINEWAI				
					Revision Description					Initial Project ref: P000529				
					Designed					Figure Number 529-001				
					Drawn					Revision B				
					Checked									
					Scale									
					AS SHOWN									
					Original Size									
					A3									

					NOT FOR CONSTRUCTION				
					THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS SIGNED AS APPROVED				
					APPROVED:				
					DATE:				
					Rev				
					Revision Description				
					Designed				
					Drawn				
					Checked				
					Scale				
					AS SHOWN				
					Original Size				
					A3				



Unit 13, 114 St Georges Bay Rd
Parnell, Auckland, 1052
Phone: +64 9 977 0462
Email: enquiries@initia.co.nz

Appendix B: GFR-Machine Borehole Logs and Photos



PROJECT: Ambury Properties				LOCATION: Tahuna/Lumsden Rds				JOB No.: 1008214.0000					
CO-ORDINATES: 5849472.01 mN (NZTM2000) 1791070.14 mE				DRILL TYPE: Tractor Rig				HOLE STARTED: 06/09/2018					
R.L.: 10.5 m				DRILL METHOD: RO				HOLE FINISHED: 06/09/2018					
DATUM: NZVD2016				DRILL FLUID:				LOGGED BY: RBE				CHECKED: RBE	
GEOLOGICAL		ENGINEERING DESCRIPTION											
GEOLOGICAL UNIT, GENERIC NAME, ORIGIN, MATERIAL COMPOSITION:		Description and Additional Observations											
Topsoil		fine SAND, organic, blackish brown											
Tauranga Group		fine SAND, loose, yellowish brown, becoming light brown with orange bands, and minor brown organic stained layers											
		1.50m: light brown											
		No recovery											
		fine SAND, saturated, grey											
		No recovery											
		No recovery. Grey silt adhering to SPT											
		sandy SILT, saturated, dilatant, light brown. Sand is fine grained											
		organic SILT, saturated, non plastic, dark brown											
		PEAT, with abundant wood, fibrous, saturated, dark brown to black											
		medium to coarse SAND, organic with peat, minor fine gravel, wet to saturated, black											
		medium to coarse SAND, organic stained, minor fine angular gravel; saturated, blackish brown											
		Core lost, not recovered. Washings of medium to coarse sand, grey in pit											
		medium to coarse SAND, with fine angular gravel, minor subrounded medium gravel; light brown to black											
		Core lost, not recovered. Washings of medium SAND, greyish brown, in pit											

COMMENTS

Hole Depth
16.95m

Scale 1:50

PROJECT: Ambury Properties				LOCATION: Tahuna/Lumsden Rds				JOB No.: 1008214.0000																													
CO-ORDINATES: 5849472.01 mN (NZTM2000) 1791070.14 mE				DRILL TYPE: Sonic Rig				HOLE STARTED: 07/09/2018																													
R.L.: 10.50m				DRILL METHOD: SNC				HOLE FINISHED: 07/09/2018																													
DATUM: NZVD2016				DRILL FLUID:				LOGGED BY: RBE CHECKED: RBE																													
GEOLOGICAL				ENGINEERING DESCRIPTION																																	
GEOLOGICAL UNIT, GENERIC NAME, ORIGIN, MATERIAL COMPOSITION:				FLUID LOSS (%)		WATER		CORE RECOVERY (%)		METHOD		CASING		TESTS		SAMPLES		RL (m)		DEPTH (m)		GRAPHIC LOG		MOISTURE / WEATHERING CONDITION		STRENGTH/DENSITY CLASSIFICATION		SHEAR STRENGTH (kPa)		COMPRESSION STRENGTH (kPa)		DEFECT SPACING (cm)		Description and Additional Observations			
Tauranga Group				25		50		80		SNC										-2		11				S										medium to coarse SAND, organic stained, minor rounded fine gravel	
						80		SNC								-3		12		medium to coarse SAND, light grey, with abundant fine gravel and minor medium gravel																	
						80		SNC								-4		13		medium SAND, some coarse sand, and minor fine rounded gravel																	
								10		SNC						-5		14																medium to coarse SAND, minor fine pumice gravel, light grey to dark greenish grey, medium dense			
						100		SNC								-6		15																medium SAND, wet, grey			
								80		SNC								-7		16														fine to medium SAND, grey, with bands of light grey silt			
								88		SPT				2/2 3/3 3/5 N=14				-8		17														silty fine SAND, saturated, light grey			
								90		SNC								-9		18														18.80m: sharp contact at base			
								90		SNC								-10		19		M		F-St										clayey SILT, low plasticity, stiff, moist, light grey mottled yellowish brown			
								100		SPT				1/1 1/2 2/3																				clayey SILT, low plasticity, moist, light grey			

COMMENTS





















Hole Depth
24.45m
Scale 1:50

PROJECT: Ambury Properties				LOCATION: Tahuna/Lumsden Rds				JOB No.: 1008214.0000			
CO-ORDINATES: 5849472.01 mN (NZTM2000) 1791070.14 mE				DRILL TYPE: Sonic Rig				HOLE STARTED: 07/09/2018			
R.L.: 10.5m				DRILL METHOD: SNC				HOLE FINISHED: 07/09/2018			
DATUM: NZVD2016				DRILL FLUID:				LOGGED BY: RBE CHECKED: RBE			
GEOLOGICAL				ENGINEERING DESCRIPTION							
GEOLOGICAL UNIT, GENERIC NAME, ORIGIN, MATERIAL COMPOSITION.				Description and Additional Observations							
25 FLUID LOSS (%) WATER CORE RECOVERY (%) METHOD CASING TESTS SAMPLES RL (m) DEPTH (m) GRAPHIC LOG MOISTURE / WEATHERING STRENGTH/DENSITY CLASSIFICATION SHEAR STRENGTH (kPa) COMPRESSION STRENGTH (kPa) DEFECT SPACING (cm)											
Tauranga Group				N=8				clayey SILT, medium plasticity, moist, grey, with minor light black mottles 20.80m: minor silty dark green inclusions 21.00m: low plasticity 22.00m: minor yellowish brown mottles 22.60m: grey and brown 22.70m: light brown 23.00m: low to medium plasticity			
				1/1 1/2 2/2 N=7							
				1/0 1/0 1/2 N=4							
				0/1 2/2 1/2 N=7							
				16 25 17 26 18 27 19 28 20 29							
				24.45m: Target depth							
COMMENTS <div style="border: 1px solid black; padding: 2px; display: inline-block;"> Hole Depth 24.45m </div>											

PROJECT: Ambury Properties				LOCATION: Tahuna/Lumsden Rds				JOB No.: 1008214.0000			
CO-ORDINATES: 5849541.82 mN (NZTM2000) 1791894.30 mE				DRILL TYPE: Sonic Rig				HOLE STARTED: 10/09/2018			
R.L.: 6.50 m				DRILL METHOD: SNC				HOLE FINISHED: 10/09/2018			
DATUM: NZVD2016				DRILL FLUID:				LOGGED BY: RBE		CHECKED: RBE	
GEOLOGICAL		ENGINEERING DESCRIPTION									
GEOLOGICAL UNIT, GENERIC NAME, ORIGIN, MATERIAL COMPOSITION:		Description and Additional Observations									
Topsoil		organic SILT peaty, non plastic, wet, black									
Tauranga Group		silty fine SAND, pumiceous, saturated, light brown									
		Sample not recovered. Traces peat at 1.5m at base of previous run									
		silty PEAT, fibrous, saturated, loosely consolidated, blackish brown									
		4.50m: Very soft, tube easily driven. SPT estimated at N=0									
		PEAT, fibrous, saturated, black									
		Barrel driven too deep, Sample displaced and not recovered									
		silty CLAY, medium to high plasticity, very soft, light green with white mottles									
		7.80m: light brown									
		8.90m: fibrous wood and roots to 9m									
		clayey SILT/silty CLAY, high plasticity, moist, light brown									
		SILT, minor clay, low to no plasticity, moist, dark brown									
No recovery. Grey silt adhering to core barrel											

COMMENTS
Hole Depth
21m


Scale 1:50

PROJECT: Ambury Properties				LOCATION: Tahuna/Lumsden Rds				JOB No.: 1008214.0000																											
CO-ORDINATES: 5849541.82 mN (NZTM2000) 1791894.30 mE				DRILL TYPE: Sonic Rig				HOLE STARTED: 10/09/2018																											
R.L.: 6.50 m				DRILL METHOD: SNC				HOLE FINISHED: 10/09/2018																											
DATUM: NZVD2016				DRILL FLUID:				LOGGED BY: RBE		CHECKED: RBE																									
GEOLOGICAL		ENGINEERING DESCRIPTION																																	
GEOLOGICAL UNIT, GENERIC NAME, ORIGIN, MATERIAL COMPOSITION.		FLUID LOSS (%)		WATER		CORE RECOVERY (%)		METHOD		CASING		TESTS		SAMPLES		RL (m)		DEPTH (m)		GRAPHIC LOG		MOISTURE CONDITION		WEATHERING		STRENGTH/DENSITY CLASSIFICATION		SHEAR STRENGTH (kPa)		COMPRESSION STRENGTH (kPa)		DEFECT SPACING (cm)		Description and Additional Observations	
		25 50 75		WATER		0		SNC				1/1 2/2 2/1 N=7				-4		11				M		S		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000					
Tauranga Group						100		SPT				1/1 0/1 1/0 N=2				-5		12				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		[CONT] No recovery. Grey silt adhering to core barrel			
						100		SNC				0/0 0/0 0/0 N=0				-6		13				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		SILT, minor clay, low plasticity, moist, light brown			
						100		SNC				1/0 0/0 0/0 N=0				-7		14				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		SILT, trace fine sand, wet to saturated, dilatant, non plastic, light brown			
						100		SNC				0/0 0/0 0/0 N=0				-8		15				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		11.80m: weakly to non dilatant			
						100		SPT				1/0 0/0 0/0 N=0				-9		16				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		12.00m: dilatant, trace organics, minor fine pumice gravel			
						100		SNC				0/0 0/0 0/0 N=0				-10		17				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		SILT, abundant organic fragments, non plastic, moist, greyish brown			
						100		SPT				0/0 0/0 0/0 N=0				-11		18				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		13.20m: brown, with abundant organics			
						100		SNC				0/0 0/0 0/0 N=0				-12		19				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		organic SILT, non plastic, moist, dark brown			
						100		SPT				0/0 0/0 0/0 N=0				-13		20				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		No recovery			
						100		SNC				0/0 0/0 0/0 N=0				-14		21				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		organic SILT, minor clay, low to no plasticity, moist, blackish brown			
				100		SPT				0/0 0/0 0/0 N=0				-15		22				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		SILT, some clay, low to no plasticity, wet, minor organics					
				100		SNC				0/0 0/0 0/0 N=0				-16		23				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		fine sandy SILT, non plastic, moist, light grey with minor brown organic staining					
				100		SPT				0/0 0/0 0/0 N=0				-17		24				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		medium SAND, saturated, grey, with white pumiceous speckles					
				100		SNC				0/0 0/0 0/0 N=0				-18		25				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000		silty fine to medium SAND, saturated, grey, to greenish grey					
				100		SPT				0/0 0/0 0/0 N=0				-19		26				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000							
				100		SNC				0/0 0/0 0/0 N=0				-20		27				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000							
				100		SPT				0/0 0/0 0/0 N=0				-21		28				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000							
				100		SNC				0/0 0/0 0/0 N=0				-22		29				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000							
				100		SPT				0/0 0/0 0/0 N=0				-23		30				M		VS		10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		1 5 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200		25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600 625 650 675 700 725 750 775 800 825 850 875 900 925 950 975 1000							
				100		SNC				0/0 0/0 0/0 N=0				-24		31																			

COMMENTS
Hole Depth
21m

Scale 1:50


Rev.: A

PROJECT: Ambury Properties				LOCATION: Tahuna/Lumsden Rds				JOB No.: 1008214.0000			
CO-ORDINATES: 5849541.82 mN (NZTM2000) 1791894.30 mE				DRILL TYPE: Sonic Rig				HOLE STARTED: 10/09/2018			
R.L.: 6.50 m				DRILL METHOD: SNC				HOLE FINISHED: 10/09/2018			
DATUM: NZVD2016				DRILL FLUID:				LOGGED BY: RBE CHECKED: RBE			
GEOLOGICAL				ENGINEERING DESCRIPTION							
GEOLOGICAL UNIT, GENERIC NAME, ORIGIN, MATERIAL COMPOSITION.				FLUID LOSS (%) WATER CORE RECOVERY (%) METHOD CASING TESTS SAMPLES RL (m) DEPTH (m)		GRAPHIC LOG MOISTURE / WEATHERING STRENGTH/DENSITY CLASSIFICATION		SHEAR STRENGTH (kPa) COMPRESSION STRENGTH (kPa) DEFECT SPACING (cm)		Description and Additional Observations	
Tauranga Group				95 SNC				F, St		clayey SILT, low plasticity, moist, greenish grey, stiff 20.90m: firm, green and light brown 21m: Target depth	
• 38/10 kPa in barrel				14 21 -15 22 -16 23 -17 24 -18 25 -19 26 -20 27 -21 28 -22 29							
COMMENTS Hole Depth 21m Scale 1:50											

Borehole 1a Core Photos



Borehole 1a: 0 to 4.7 m




Borehole 1a: 4.7 to 9.0 m




Borehole 1a: 9.0 to 12.0 m




Borehole 1a: 12.0 to 16.0 m



Borehole 1a: 16.0 to 19.3 m



Borehole 1a: 19.3 to 22.0 m



Borehole 1a: 22.0 to 24.45 m

Borehole 2 Core Photos



Borehole 2: 0 to 3.7 m




Borehole 2: 3.7 to 9.5 m



Borehole 2: 9.5 to 12.45 m



Borehole 2: 12.45 to 16.0 m



Borehole 2: 16.0 to 18.45 m



Borehole 2: 18.45 to 21.3 m





Borehole 2: 21.3 to 22.5 m

Appendix C: GFR-Cone Penetrometer Test Logs





Classification by
Robertson 1990



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT01
Project ID:		Client:	INITIA	Date:	5/9/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
	S 37.48027, E 175.16078			File:	CPT01.cpt		

**Classification by
Robertson 1990**





TARGET DEPTH



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT02
Project ID:		Client:	INITIA	Date:	5/9/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/2	Fig.:	
	S 37.48006, E 175.16313			File:	CPT02.cpt		

**Classification by
Robertson 1990**





TARGET DEPTH



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT04
Project ID:	P-000529	Client:	INITIA	Date:	5/9/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/2	Fig.:	
	S 37.47971, E 175.16782			File:	CPT04.cpt		

**Classification by
Robertson 1990**



TARGET DEPTH

Rf [%]





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150



Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT05
Project ID:	P-000529	Client:	INITIA	Date:	5/9/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
	S 37.47955, E 175.17014			File:	CPT05.cpt		

Classification by
Robertson 1990



NO WATER READING - HOLE COLLAPSED AT 1.15M



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150





Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT06
Project ID:	P-000529	Client:	INITIA	Date:	5/9/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/2	Fig.:	
S 37.48188, E 175.16107				File:	CPT06.cpt		



Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT07
Project ID:	P-000529	Client:	INITIA	Date:	5/9/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/2	Fig.:	
S 37.48152, E 175.16328				File:	CPT07.cpt		

Classification by
Robertson 1990





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150



Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT08
Project ID:	p-000529	Client:	INITIA	Date:	6/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48152, E 175.16568				File:	CPT08.cpt		

Classification by
Robertson 1990



TARGET DEPTH





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150



Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT09
Project ID:	P-000529	Client:	INITIA	Date:	6/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/2	Fig.:	
	S 37.48129, E 175.16801			File:	CPT09.cpt		



**Classification by
Robertson 1990**



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT10
Project ID:	P-000529	Client:	INITIA	Date:	6/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48115, E 175.17032				File:	CPT10.cpt		

**Classification by
Robertson 1990**




REFUSAL FROM HIGH QC




Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150





Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT11
Project ID:	P-0000529	Client:	INITIA	Date:	6/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48384, E 175.16191				File:	CPT11.cpt		








Classification by
Robertson 1990





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT15
Project ID:	P-000529	Client:	INITIA	Date:	7/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
	S 37.48305, E 175.17047			File:	CPT15.cpt		




Classification by
Robertson 1990





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150



Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT18
Project ID:	P-000529	Client:	INITIA	Date:	7/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
	S 37.48512, E 175.16832			File:	CPT18.cpt		









Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT21
Project ID:	P-000529	Client:	INITIA	Date:	7/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48623, E 175.16447				File:	CPT21.cpt		

Classification by
Robertson 1990



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT22
Project ID:	P-000529	Client:	INITIA	Date:	7/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48719, E 175.16631				File:	CPT22.cpt		

Classification by
Robertson 1990

- Gravelly sand to sand (7)
- Sands; clean sand to silty sand (6)
- Sand mixtures; silty sand to sandy silt (5)
- Organic soils-peats (2)

Clays; clay to silty clay (3)

Organic soils-peats (2)

Sensitive, fine grained (1)

Clays; clay to silty clay (3)

Sensitive, fine grained (1)

Clays; clay to silty clay (3)

Sensitive, fine grained (1)

Clays; clay to silty clay (3)

Sensitive, fine grained (1)

Sand mixtures; silty sand to sandy silt (5)

Silt mixtures; clayey silt to silty clay (4)

Clays; clay to silty clay (3)

Silt mixtures; clayey silt to silty clay (4)

Clays; clay to silty clay (3)

Silt mixtures; clayey silt to silty clay (4)

Sensitive, fine grained (1)


Silt mixtures; clayey silt to silty clay (4)

Sand mixtures; silty sand to sandy silt (5)

Clays; clay to silty clay (3)


Sand mixtures; silty sand to sandy silt (5)


REFUSAL FROM ANCHOR FAILURE




Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT23
Project ID:	P-000529	Client:	INITIA	Date:	7/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48687, E 175.16838				File:	CPT23.cpt		





Classification by
Robertson 1990



Sands; clean sand to silty sand (6)

Clays; clay to silty clay (3)

Sands; clean sand to silty sand (6)

Sand mixtures; silty sand to sandy silt (5)

Silt mixtures; clayey silt to silty clay (4)

Clays; clay to silty clay (3)

Sand mixtures; silty sand to sandy silt (5)

Sands; clean sand to silty sand (6)

Sand mixtures; silty sand to sandy silt (5)

Sensitive, fine grained (1)

Silt mixtures; clayey silt to silty clay (4)

Sensitive, fine grained (1)

Silt mixtures; clayey silt to silty clay (4)


Sand mixtures; silty sand to sandy silt (5)

Silt mixtures; clayey silt to silty clay (4)

Sand mixtures; silty sand to sandy silt (5)

Silt mixtures; clayey silt to silty clay (4)

Silt mixtures; clayey silt to silty clay (4)



REFUSAL FROM ANCHOR FAILURE (FIRM QC)




Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT26
Project ID:	P-000529	Client:	INITIA	Date:	7/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48804, E 176.16447				File:	CPT26.cpt		

Classification by
Robertson 1990



	Very stiff sand to clayey sand (8)
	Very stiff fine grained (9)
	Silt mixtures; clayey silt to silty clay (4)
	Sand mixtures; silty sand to sandy silt (5)
	Clays; clay to silty clay (3)
	Sands; clean sand to silty sand (6)
	Clays; clay to silty clay (3)
	Silt mixtures; clayey silt to silty clay (4)
	Sands; clean sand to silty sand (6)



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150


Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT27
Project ID:	P-000529	Client:	INITIA	Date:	10/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48860, E 175.16864				File:	CPT27.cpt		

**Classification by
Robertson 1990**




Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT28
Project ID:	P-000529	Client:	INITIA	Date:	10/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48830, E 175.17116				File:	CPT28A.cpt		



Classification by
Robertson 1990



	Gravely sand to sand (7)
	Very stiff fine grained (9)
	Sands; clean sand to silty sand (6)
	Sand mixtures; silty sand to sandy silt (5)
	Sands; clean sand to silty sand (6)
	Very stiff fine grained (9)
	Sand mixtures; silty sand to sandy silt (5)
	Silt mixtures; clayey silt to silty clay (4)
	Sand mixtures; silty sand to sandy silt (5)
	Silt mixtures; clayey silt to silty clay (4)
	Clays; clay to silty clay (3)
	Sand mixtures; silty sand to sandy silt (5)
	Sands; clean sand to silty sand (6)



Cone No: 4696
Tip area [cm2]: 10
Sleeve area [cm2]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT30
Project ID:	P-000529	Client:	INITIA	Date:	10/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48946, E 175.16418				File:	CPT30.cpt		

Classification by
Robertson 1990





REFUSAL FROM ANCHOR FAILURE (FIRM QC + FS)
NO WATER READING - HOLE COLLAPSED AT 0.20M



Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150

Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT31
Project ID:	P-000529	Client:	INITIA	Date:	10/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48962, E 175.16664				File:	CPT31.cpt		

Classification by
Robertson 1990





TARGET DEPTH





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150


Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT32
Project ID:	P-000529	Client:	INITIA	Date:	10/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
	S 37.49004, E 175.16878			File:	CPT32.cpt		


























Cone No: 4696
Tip area [cm2]: 10
Sleeve area [cm2]: 150


Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT47
Project ID:	P-000529	Client:	INITIA	Date:	14/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48668, E 175.17799				File:	CPT47.cpt		


Classification by
Robertson 1990





Cone No: 4696
Tip area [cm²]: 10
Sleeve area [cm²]: 150


Location:	OHINEWAI	Position:	X: 0.00 m, Y: 0.00 m	Ground level:	0.00	Test No.:	CPT48
Project ID:	P-000529	Client:	INITIA	Date:	14/09/2018	Scale:	1 : 112
Project:	TAHUNA RD			Page:	1/1	Fig.:	
S 37.48680, E 175.17578				File:	CPT48.cpt		















































Appendix D: GFR-Test Pit Investigation Logs







	TEST PIT LOG		HOLE NO.: TP01			
	CLIENT: Ambury properties PROJECT: Sleepyhead Ohinewai		JOB NO.: P-000529			
SITE LOCATION: Lumsden Rd Block		ELEVATION: 10m		START DATE: 31/10/2018		
CO-ORDINATES: 1791143mE, 5849411mN (NZTM)		DRILLER: Heb		END DATE: 31/10/2018		
CONTRACTOR: Broughton		RIG: 12t Ex		LOGGED BY: KND		
MATERIAL DESCRIPTION (See Classification & Symbolology sheet for details)	SAMPLES	DEPTH (m)	LEGEND	SCALA PENETROMETER (Blows / 0mm)	VANE SHEAR STRENGTH (kPa) Vane:	WATER
Topsoil		0.0	TS	2 4 6 8 10 12 14 16 18	50 100 150 200	
SAND; yellowish brown, with light brown and orange bands. Loose; moist; sand, fine.		0.2	TS			
		0.4	TS			
		0.6	TS			
	B	0.8	TS			
		1.0	TS			
SAND, with some gravel; yellowish brown, white. Loose; moist; sand, fine; gravel, fine; (Pumiceous gravel).		1.2	B			
		1.4	B			
		1.6	B			
		1.8	B			
SAND; grey. Saturated; sand, fine; some fibrous peat / organics in the base of the excavation. .		2.0	B			
Running sands - pit collapse EOH: 2.00m		2.2				
		2.4				
		2.6				
		2.8				
REMARKS						
						
WATER ▼ Standing Water Level ↙ Out flow ↘ In flow						
INVESTIGATION TYPE <input type="checkbox"/> Hand Auger <input checked="" type="checkbox"/> Test Pit						

	TEST PIT LOG		HOLE NO.: TP02			
	CLIENT: Ambury properties PROJECT: Sleepyhead Ohinewai		JOB NO.: P-000529			
SITE LOCATION: Lumsden Rd Block		START DATE: 31/10/2018				
CO-ORDINATES: 1791213mE, 5849592mN (NZTM)		END DATE: 31/10/2018				
CONTRACTOR: Broughton		LOGGED BY: KND				
RIG: 12t Ex		ELEVATION: 10m				
DRILLER: Heb						
MATERIAL DESCRIPTION (See Classification & Symbology sheet for details)	SAMPLES	DEPTH (m)	LEGEND	SCALA PENETROMETER (Blows / 0mm)	VANE SHEAR STRENGTH (kPa) Vane:	WATER
Topsoil		0.2	TS			
SAND, with trace silt; yellowish brown. Loose; moist; sand, fine to medium.		0.4				
SAND, with some gravel; light brown mottled white. Moist; sand, fine to coarse; gravel, fine to medium; (Pumiceous gravel).		0.6				
		0.8				
		1.0				
		1.2				
		1.4				
		1.6				
		1.8				
		2.0				
		2.2				
		2.4				
EOH: 2.50m		2.6				
		2.8				
REMARKS						
						
WATER ▼ Standing Water Level ↙ Out flow ↘ In flow						
INVESTIGATION TYPE <input type="checkbox"/> Hand Auger <input checked="" type="checkbox"/> Test Pit						

	TEST PIT LOG		HOLE NO.: TP03			
	CLIENT: Ambury properties PROJECT: Sleepyhead Ohinewai		JOB NO.: P-000529			
SITE LOCATION: Lumsden Rd Block CO-ORDINATES: 1791454mE, 5849618mN (NZTM) CONTRACTOR: Broughton RIG: 12t Ex		ELEVATION: 8m DRILLER: Heb		START DATE: 31/10/2018 END DATE: 31/10/2018 LOGGED BY: KND		
MATERIAL DESCRIPTION (See Classification & Symbolology sheet for details)	SAMPLES	DEPTH (m)	LEGEND	SCALA PENETROMETER (Blows / 0mm) 2 4 6 8 10 12 14 16 18	VANE SHEAR STRENGTH (kPa) Vane: 50 100 150 200 Values	WATER
Topsoil						
SAND, with some gravel; light brown mottled orange and brown staining. Moist; sand, fine; gravel, fine to medium; FILL.		0.2				
SILT, with minor sand. Sand, fine; Buried Topsoil FILL?.		0.4				
SAND, with minor gravel; yellowish brown, with light brown and orange bands.. Wet; sand, fine; gravel, fine to coarse.		0.6				
SAND; light grey. Saturated; sand, fine.		0.8				
		1.0				
		1.2				
	B	1.4				
		1.6				
SAND, with some silt; light grey to light brown. Saturated; sand, fine; Occasional tree roots (up to 50mm dia.).		1.8				
		2.0				
		2.2				
		2.4				
		2.6				
	2.8					
2.7m: Flowing water						
REMARKS						
						
<div><div>WATER ▼ Standing Water Level ↙ Out flow ↘ In flow</div><div>INVESTIGATION TYPE <input type="checkbox"/> Hand Auger <input checked="" type="checkbox"/> Test Pit</div></div>						

	TEST PIT LOG					HOLE NO.: TP03										
	CLIENT: Ambury properties PROJECT: Sleepyhead Ohinewai					JOB NO.: P-000529										
SITE LOCATION: Lumsden Rd Block			ELEVATION: 8m			START DATE: 31/10/2018										
CO-ORDINATES: 1791454mE, 5849618mN (NZTM)			DRILLER: Heb			END DATE: 31/10/2018										
CONTRACTOR: Broughton			RIG: 12t Ex			LOGGED BY: KND										
MATERIAL DESCRIPTION (See Classification & Symbolology sheet for details)	SAMPLES	DEPTH (m)	LEGEND	SCALA PENETROMETER (Blows / 0mm)								VANE SHEAR STRENGTH (kPa) Vane:				WATER
				2	4	6	8	10	12	14	16	18	50	100	150	
[CONT] SAND, with some silt; light grey to light brown. Saturated; sand, fine; Occasional tree roots (up to 50mm dia.). EOH: 3.20m	B	3.2														
		3.4														
		3.6														
		3.8														
		4.0														
		4.2														
		4.4														
		4.6														
		4.8														
		5.0														
		5.2														
		5.4														
		5.6														
		5.8														
			REMARKS													
			WATER												INVESTIGATION TYPE	
			 Standing Water Level												<input type="checkbox"/> Hand Auger	
			 Out flow												<input checked="" type="checkbox"/> Test Pit	
			 In flow													

	TEST PIT LOG		HOLE NO.: TP04			
	CLIENT: Ambury properties PROJECT: Sleepyhead Ohinewai		JOB NO.: P-000529			
SITE LOCATION: Lumsden Rd Block		START DATE: 31/10/2018				
CO-ORDINATES: 1791766mE, 5849601mN (NZTM)		END DATE: 31/10/2018				
CONTRACTOR: Broughton		LOGGED BY: KND				
RIG: 12t Ex		ELEVATION: 8m				
DRILLER: Heb						
MATERIAL DESCRIPTION (See Classification & Symbolology sheet for details)	SAMPLES	DEPTH (m)	LEGEND	SCALA PENETROMETER (Blows / 0mm)	VANE SHEAR STRENGTH (kPa) Vane:	WATER
Topsoil				2 4 6 8 10 12 14 16 18	50 100 150 200	
SAND, with some gravel; yellowish brown mottled orange white. Sand, fine to coarse; gravel, fine to medium; (Pumiceous Gravel).		0.2 0.4 0.6 0.8 1.0 1.2				
SAND, with minor silt; light grey. Saturated; sand, fine.		1.4 1.6 1.8 2.0 2.2 2.4 2.6 2.8				
EOH: 2.70m						
2.7m - 2.7m: large tree roots / stumps in base of hole. Hole collapsed at 2.7m						
REMARKS						
						
WATER ▼ Standing Water Level ↗ Out flow ↘ In flow						
INVESTIGATION TYPE <input type="checkbox"/> Hand Auger <input checked="" type="checkbox"/> Test Pit						

	TEST PIT LOG		HOLE NO.: TP06			
	CLIENT: Ambury properties PROJECT: Sleepyhead Ohinewai		JOB NO.: P-000529			
SITE LOCATION: Lumsden Rd Block CO-ORDINATES: 1791468mE, 5849334mN (NZTM) CONTRACTOR: Broughton RIG: 12t Ex		ELEVATION: 8m DRILLER: Heb		START DATE: 31/10/2018 END DATE: 31/10/2018 LOGGED BY: KND		
MATERIAL DESCRIPTION (See Classification & Symbolology sheet for details)	SAMPLES	DEPTH (m)	LEGEND	SCALA PENETROMETER (Blows / 0mm) 2 4 6 8 10 12 14 16 18	VANE SHEAR STRENGTH (kPa) Vane: 50 100 150 200 Values	WATER
Topsoil		0.0	TS			
SAND; yellowish brown with orange bands. Moist; sand, fine.		0.2	TS			
		0.4	TS			
SAND; grey. Saturated; sand, fine.		0.6	TS			
		0.8	TS			
		1.0	TS			
		1.2	TS			
		1.4	TS			
		1.6	TS			
		1.8	TS			
		2.0	TS			
		2.2	TS			
		2.4	TS			
SILT; dark brown. Saturated; PEAT. EOH: 2.50m		2.6	TS			
	2.8	TS				
REMARKS						
			<div>WATER ▼ Standing Water Level ↵ Out flow ▷ In flow</div> <div>INVESTIGATION TYPE <input type="checkbox"/> Hand Auger <input checked="" type="checkbox"/> Test Pit</div>			

Appendix E: GFR-Laboratory Testing Results



Test Number: 183103

Report Number: 30607T

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTD

Clients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded SpecimensDate Sampled: 31st October 2018Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand with Pumice Gravels – TP01 1.3 – 1.6m**

Source: Lumsden Road

Job: Block Trail Pits

Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.

for STEVENSON AGGREGATES LTD


T A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand with Pumice Gravels – TP01 1.3 – 1.6m	Test No:	183103
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	85.0%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	-	-	100	100	100	100	99	99	98	95	63	18	3
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Dry) = Oven Dried Sample	(Wet) = % passing finest sieve obtained by difference										Fineness Modulus:			
											-			



TEST RESULTS

Material:	Sand with Pumice Gravels – TP01 1.3 – 1.6m	Test No:	183103
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample **Two Hour Delay (Before Compaction)**

		Result		
Compaction effort		NZ Standard Compaction		
Surcharge mass	(kg)	4.0		
Period of Air Cure	(Days)	3		
Period of Soaking	(Days)	4		
Lime Added	(%)	1	1	1
Cement Added	(%)	3	4	5
Dry density	(t/m ³)	0.80	0.80	0.80
Compacted Water Content	(%)	76.9	77.8	77.3
Soaked Water Content	(%)	64.8	66.6	67.5
Swell	(%)	-0.2	-0.4	-0.6
Rate of penetration	(mm/min)	1	1	1
Depth CBR recorded	(mm)	5.0	5.0	5.0
California Bearing Ratio	CBR	10%	10%	11%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Test Number: 183102

Report Number: 30608T

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTD

Clients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded Specimens

Date Sampled: 31st October 2018

Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand Yellow Brown with Orange Bands – TP01 0.5 – 1.0m**

Source: Lumsden Road

Job: Block Trail Pits

Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.

for STEVENSON AGGREGATES LTD


T A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand Yellow Brown with Orange Bands – TP01 0.5 – 1.0m	Test No:	183102
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	64.3%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	-	-	-	100	100	100	99	98	96	90	49	10	5
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
{Dry} = Oven Dried Sample		{Wet} = % passing finest sieve obtained by difference								Finesness Modulus:		-		



TEST RESULTS

Material:	Sand Yellow Brown with Orange Bands – TP01 0.5 – 1.0m	Test No:	183102
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample Two Hour Delay (Before Compaction)

		Result			
Compaction effort		NZ Standard Compaction			
Surcharge mass	(kg)	4.0			
Period of Air Cure	(Days)	3			
Period of Soaking	(Days)	4			
Lime Added	(%)	Natural	1	1	1
Cement Added	(%)		3	4	5
Dry density	(t/m ³)	0.86	0.88	0.88	0.90
Compacted Water Content	(%)	64.6	61.5	61.4	58.5
Soaked Water Content	(%)	62.7	56.6	56.5	55.6
Swell	(%)	0.0	-0.2	-0.4	0.0
Rate of penetration	(mm/min)	1	1	1	1
Depth CBR recorded	(mm)	5.0	5.0	5.0	5.0
California Bearing Ratio	CBR	8%	8%	8%	12%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Test Number: 183104

Report Number: 30609T

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTD

Clients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded Specimens

Date Sampled: 31st October 2018

Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand with Pumice Gravels – TP02 2.0 – 2.5m**

Source: Lumsden Road

Job: Block Trail Pits

Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.

for STEVENSON AGGREGATES LTD


T A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand with Pumice Gravels – TP02 2.0 – 2.5m	Test No:	183104
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	101.1%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	100	100	99	98	98	97	95	93	91	88	64	32	26
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Dry) = Oven Dried Sample	(Wet) = % passing finest sieve obtained by difference								Fineness Modulus:		-			



TEST RESULTS

Material:	Sand with Pumice Gravels – TP02 2.0 – 2.5m	Test No:	183104
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample Two Hour Delay (Before Compaction)

	Result			
Compaction effort	NZ Standard Compaction			
Surcharge mass (kg)	4.0			
Period of Air Cure (Days)	3			
Period of Soaking (Days)	4			
Lime Added (%)	Natural	1	1	1
Cement Added (%)		3	4	5
Dry density (t/m ³)	0.70	0.72	0.72	0.72
Compacted Water Content (%)	100.5	94.7	93.3	91.5
Soaked Water Content (%)	84.6	75.0	78.6	76.6
Swell (%)	-0.6	-0.2	-0.4	-0.4
Rate of penetration (mm/min)	1	1	1	1
Depth CBR recorded (mm)	5.0	5.0	5.0	5.0
California Bearing Ratio CBR	6%	11%	11%	11%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Test Number: 183105

Report Number: 30610T

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTD

Clients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded Specimens

Date Sampled: 31st October 2018

Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand Yellow Brown with Orange Bands – TP05 0.5 – 0.8m**

Source: Lumsden Road

Job: Block Trail Pits

Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.

for STEVENSON AGGREGATES LTD



T A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand Yellow Brown with Orange Bands – TP05 0.5 – 0.8m	Test No:	183105
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	79.3%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	-	100	100	100	99	98	97	95	91	84	47	13	8
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Dry) = Oven Dried Sample	(Wet) = % passing finest sieve obtained by difference										Fineness Modulus:			
											-			



TEST RESULTS

Material:	Sand Yellow Brown with Orange Bands – TP05 0.5 – 0.8m	Test No:	183105
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample **Two Hour Delay (Before Compaction)**

		Result		
Compaction effort		NZ Standard Compaction		
Surcharge mass	(kg)	4.0		
Period of Air Cure	(Days)	3		
Period of Soaking	(Days)	4		
Lime Added	(%)	1	1	1
Cement Added	(%)	3	4	5
Dry density	(t/m ³)	0.78	0.78	0.78
Compacted Water Content	(%)	73.2	75.3	73.5
Soaked Water Content	(%)	69.2	68.9	67.5
Swell	(%)	0.0	0.0	-0.2
Rate of penetration	(mm/min)	1	1	1
Depth CBR recorded	(mm)	5.0	5.0	5.0
California Bearing Ratio	CBR	8%	8%	10%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Test Number: 183106

Report Number: 30611T

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTD

Clients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded Specimens

Date Sampled: 31st October 2018

Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand – Grey Wet – TP03 1.3 – 1.6m**

Source: Lumsden Road

Job: Block Trail Pits

Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.

for STEVENSON AGGREGATES LTD


T A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand – Grey Wet – TP03 1.3 – 1.6m	Test No:	183106
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	82.4%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	-	-	-	-	100	100	100	100	100	99	81	43	29
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Dry) = Oven Dried Sample	(Wet) = % passing finest sieve obtained by difference								Fineness Modulus:		-			



TEST RESULTS

Material:	Sand – Grey Wet – TP03 1.3 – 1.6m	Test No:	183106
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample **Two Hour Delay (Before Compaction)**

	Result		
Compaction effort	NZ Standard Compaction		
Surcharge mass (kg)	4.0		
Period of Air Cure (Days)	3		
Period of Soaking (Days)	4		
Lime Added (%)	1	1	1
Cement Added (%)	3	4	5
Dry density (t/m ³)	0.78	0.80	0.80
Compacted Water Content (%)	77.5	75.3	74.0
Soaked Water Content (%)	70.4	67.5	66.5
Swell (%)	-0.8	-1.0	-1.6
Rate of penetration (mm/min)	1	1	1
Depth CBR recorded (mm)	5.0	5.0	5.0
California Bearing Ratio CBR	3%	5%	6%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Test Number: 183107

Report Number: 30612T

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTDClients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded SpecimensDate Sampled: 31st October 2018Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand – Grey Light Brown – TP03 3.1m**

Source: Lumsden Road

Job: Block Trail Pits

Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.

for STEVENSON AGGREGATES LTD


T A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand – Grey Light Brown – TP03 3.1m	Test No:	183107
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	78.2%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	-	-	-	-	100	100	100	100	100	100	95	71	61
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Dry) = Oven Dried Sample	(Wet) = % passing finest sieve obtained by difference										Finesness Modulus:			
											-			



TEST RESULTS

Material:	Sand – Grey Light Brown – TP03 3.1m	Test No:	183107
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample **Two Hour Delay (Before Compaction)**

		Result		
Compaction effort		NZ Standard Compaction		
Surcharge mass	(kg)	4.0		
Period of Air Cure	(Days)	3		
Period of Soaking	(Days)	4		
Lime Added	(%)	1	1	1
Cement Added	(%)	3	4	5
Dry density	(t/m ³)	0.82	0.82	0.84
Compacted Water Content	(%)	73.1	72.9	71.5
Soaked Water Content	(%)	66.5	66.4	65.9
Swell	(%)	-3.0	-3.2	-2.2
Rate of penetration	(mm/min)	1	1	1
Depth CBR recorded	(mm)	5.0	5.0	5.0
California Bearing Ratio	CBR	3%	3%	3.5%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Test Number: 183108

Report Number: 306137

Date of Issue: 13th November 2018

Page 1 of 3 Pages

FINAL REPORT FOR INITIA LTD

Clients Address: PO Box 47647
Ponsonby
AUCKLAND 1144

Attention: Kent Dalziel

Reference: P-000529

Subject: **AGGREGATE TESTING**

Clients Instructions: Conduct the tests as detailed below on the aggregate sample received

Test Methods: 1. NZS4402: 1986: Test
2.1 Determination of the Water Content
2.8.1: Particle Size Distribution – Wet Sieve Method
6.1.1: California Bearing Ratio (CBR) – Remoulded SpecimensDate Sampled: 31st October 2018Date Received: 31st October 2018

Date of Tests: October – November 2018

Description of Sample: **Sand – Grey – TP05 2.5 – 2.8m**

Source: Lumsden Road

Job: Block Trail Pits


Notes: i. Field sample received in its natural state.
ii. Sampling of aggregate is not covered by this report.for STEVENSON AGGREGATES LTDT A WHITMORE
IANZ APPROVED SIGNATORY

TEST RESULTS

Material:	Sand – Grey – TP05 2.5 – 2.8m	Test No:	183108
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

TEST METHOD	RESULT	SPECIFICATION
Particle Size Distribution (Wet Sieve Method)	See below	-
Water Content (Natural)	73.5%	-

SIEVE SIZE (mm)	37.5	19	13.2	9.5	6.7	4.75	2.36	1.18	.600	.425	.300	.150	.075	.063
% PASSING SIEVE (Wet)	-	-	-	-	-	100	100	100	100	100	99	95	65	51
MAXIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
MINIMUM SPECIFIED LIMIT	-	-	-	-	-	-	-	-	-	-	-	-	-	-
(Dry) = Oven Dried Sample	(Wet) = % passing finest sieve obtained by difference										Fineness Modulus:			
											-			



TEST RESULTS

Material:	Sand – Grey – TP05 2.5 – 2.8m	Test No:	183108
Source:	Lumsden Road	Date Sampled:	31 st October 2018
Job:	Block Trail Pits	Reference No.:	P-000529

CALIFORNIAN BEARING RATIO - Laboratory Batched Sample **Two Hour Delay (Before Compaction)**

		Result			
Compaction effort		NZ Standard Compaction			
Surcharge mass	(kg)	4.0			
Period of Air Cure	(Days)	3			
Period of Soaking	(Days)	4			
Lime Added	(%)	Natural	1	1	1
Cement Added	(%)		3	4	5
Dry density	(t/m ³)	0.82	0.84	0.84	0.84
Compacted Water Content	(%)	72.8	69.1	69.0	67.9
Soaked Water Content	(%)	68.5	65.1	64.1	62.0
Swell	(%)	-1.8	-1.4	-1.4	-1.6
Rate of penetration	(mm/min)	1	1	1	1
Depth CBR recorded	(mm)	5.0	5.0	5.0	5.0
California Bearing Ratio	CBR	3%	3.5%	3.5%	6%

- Notes:
- i. Negative swell implies shrinkage.
 - ii. Test performed on fraction passing 19mm sieve (100%).
 - iii. Lime and cement added as a percentage of dry mass.

Appendix F: GFR-Historical Investigation Data



LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 6.08m

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT

ROCK WEATHERING
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

TEST RESULT
5 - 10 - 50

CORE LOSS/LIFT %
5 - 10 - 50

DEPTH H.A.D. m
Core size: casing

GRAPHIC LOG
50 - 10 - 5 - 1

SPACING OF NATURAL DEFECTS (cms)
50 - 10 - 5 - 1

DEFECT DESCRIPTION

(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)

SOIL DESCRIPTION

(consistency, relative density, water content, plasticity, grading, group symbol etc.)

DATE/DEPTH
R.O.D.

WATER LEVEL
Date

DRILL WATER LOSS %
0 - 100

WATER TEST RESULT

TAURANGA GROUP

V. wk lt br - br SANDY SILT with silty peat layer (<10mm thk), gravel layers (<15mm)

V. wk lt grey olive f SANDY SILT

V. wk lt br - grey SANDY SILT with rare gravel (<10mm)

V. wk olive grey SANDY SILT with pumiceous gravels (<10mm) grading to f SANDY SILT

V. wk greyish grn CLAYEY SILT

V. wk greyish grn CLAYEY SILT lam with carb plant material (<2mm thk)

V. wk lt grey SILT grading into greenish grey - greyish grn CLAYEY SILT, abund pumiceous aggregate & wood frags grading to greyish grn SILT with rare plant material & yellowish grey pumiceous gravels

V. wk greyish grn v f - f SANDY SILT, massive, bedded

V. wk greyish grn CLAYEY SILT with rare sand

V. wk greenish grey - crs SANDY SILT

V. wk greenish blue grn - dusky blue grn sl silty med to pebbly SAND, 2:1 volcanic rock frags to pumice.

V. wk lt olive grey SILT interbedded with peat (<60mm thk)

V. wk greenish grey crs - pebbly SAND 90% pumice, well rounded pebble (<20mm) pumice (<120mm)

DRILLER: BROWN BROS

STARTED: 2.7.84

FINISHED: 27.7.84

DRILL: FAILING

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

Spacing of natural defects. Defects/m of core

PROJECT: OHINEWAI

HOLE NO: 9782

LENGTH: 162.30m

CORE BOXES: 19

LOGGED: A.H.M.

DATE: 5-7-84

TRACED: R.B.K.

CHECKED: D.E.W.

ORIGINAL SCALE

1:100

INVESTIGATION GEOLOGY LTD consulting geologists		PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY				HOLE No. 9782							
		FEATURE LOCATION		CO-ORDINATES 632 829.18 N 336 733.04 E									
LOG OF DRILL HOLE		ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 6.08m											
DESCRIPTION OF CORE	ROCK WEATHERING	RELATIVE STRENGTH	TEST RESULT	CORE LOSS/LIFT	DEPTH H.A.D.	GRAPHIC LOG	SPACING OF NATURAL DEFECTS	DEFECT DESCRIPTION (JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.) SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)	DATE/DEPTH	ROD	WATER LEVEL	DRILL WATER LOSS	WATER TEST RESULT
WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT	SW MW HW	S MS MW W		5 10 50	m		(cm)					0-100	
<div style="display: flex; justify-content: space-between;"> <div style="width: 20%;"> <p style="text-align: center;">TAURANGA GROUP</p> <hr/> <p style="text-align: center;">MANGAKOTUKU SILTSTONE</p> <hr/> <p style="text-align: center;">SANDSTONE</p> <hr/> <p style="text-align: center;">PUKEMIRO</p> </div> <div style="width: 80%;"> <p>Mod-wk, dark green CLAYEY SILTSTONE with rare carb. fragments</p> <p>Mod-strong, dark greenish-grey muddy SANDSTONE - glauconitic - indications of bedding sub-horiz</p> <p>- siltstone laminae increasing with depth</p> <p>Mod-wk, greyish green SILTY CLAYSTONE with thin sandy laminae</p> </div> </div>													
<div style="display: flex; justify-content: space-between;"> <div style="width: 20%;"> <p>103</p><p>104</p><p>105</p><p>106</p><p>107</p><p>108</p><p>109</p><p>110</p><p>111</p><p>112</p><p>113</p><p>114</p><p>115</p><p>116</p><p>117</p><p>118</p><p>119</p><p>120</p><p>121</p><p>122</p><p>123</p><p>124</p><p>125</p> </div> <div style="width: 80%;"> <p>Tauranga Group logged by W. Leask of State Coal Mines</p> <p>CORE NOT SEEN BY R.L. 103.75 - 107.50m</p> <p>core highly disturbed during drilling</p> <p>jt, 30°, sm, slick</p> <p>jfs, sub-horiz, sm, 20-50mm apart</p> <p>jt, 30°, sm, slick</p> <p>jt, sub-horiz, sm, slick</p> <p>core highly disturbed during drilling</p> <p>CORE NOT SEEN</p> <p>contact, sharp, sub-horiz. with thin layer silty clay</p> <p>sub-horiz, 10-20mm thick silty clay layers present, firm, moist</p> <p>highly plastic, 100mm apart, drilling induced</p> <p>sub-horiz, 5-10mm thick SILTY CLAY layer</p> <p>horiz, 10mm thick SILTY CLAY layer</p> </div> </div>													
DRILLER: BROWN BROS STARTED: 16-7-84 FINISHED: 27-7-84 DRILL: FAILING		WEATHERING UW - Unweathered SW - Slightly weathered MW - Moderately weathered HW - Highly weathered CW - Completely weathered		RELATIVE STRENGTH VS - Very Strong S - Strong MS - Moderately strong MW - Moderately weak W - Weak VW - Very weak		DEFECT LOG 		PROJECT: OHINEWAI HOLE NO: 9782 LENGTH: 162.30m CORE BOXES: 19		LOGGED: D.E.W. DATE: JULY 1984 TRACED: R.B.K. CHECKED: B.W.R. ORIGINAL SCALE: 1:100			
EXPLANATION Tauranga Group logged by W. Leask of State Coal						SHEET 2 OF 4 DRG NO							

INVESTIGATION GEOLOGY LTD

consulting geologists

PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY

HOLE

No.

9783

FEATURE LOCATION

CO-ORDINATES 632 339.9 N

337 239.5 E

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 6.4m

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT

ROCK WEATHERING

RELATIVE STRENGTH

TEST RESULT

CORE LOSS/ LIFT %

DEPTH H A D

Core size, casing

GRAPHIC LOG

SPACING OF NATURAL DEFECTS

DEFECT DESCRIPTION (JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)

SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)

DATE/DEPTH

ROD

WATER LEVEL

DRILL WATER LOSS %

WATER TEST RESULT

Drillers logs indicate peat & clay
Very wk, light grey fine SAND (pumice)
Very wk, light grey CLAYEY SILT

Drillers log indicates very wk SILTY SAND
Very wk, light brown SILTY CLAY, carbonaceous
Very wk, light grey SILTY CLAY
Very wk, mxd light br., light grey SILTY CLAY

Very wk, grey SANDY SILT

Very wk, greyish-green SANDY SILT with SILTY CLAY laminae
Very wk light brown SILTY CLAY carbonaceous
Very wk, light grey, SILTY CLAY carb. grading to a darker gr-br. near base

Very wk, br. SAND grading to a very wk, fine sandy gravel

Very wk, light br. SILTY CLAY carb. with fine sandy horizons
Wk, light bluish - grey fine SANDY SILTSTONE

Wk, light bluish-grey, muddy fine SANDSTONE, graded quartz-feldspar
Indications of bedding at 10°

Very wk, bluish-grey SAND, graded, bedded

Strong-mod. strong bluish-grey SANDSTONE graded

Drillers log indicates fine SAND & GRAVEL
Very wk, bluish-grey GRAVELLY SAND coarse qtz-feldspar
Very wk, dk, red-br. PEAT laminated
Very wk, green-gr. SILT & bl-gr SAND interbedded
Very wk, dk, red-br. PEAT with wood fragments, laminated
Very wk, greyish white SANDY SILT. Pumice slightly carbonaceous

Wk- very wk, red.-br PEAT, laminated

DRILLER:
BROWN BROSSTARTED:
5 - 8 - 83FINISHED:
19 - 9 - 83DRILL:
FAILING

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

(mm)
Spacing of natural defects
Defects/m of core

EXPLANATION

PROJECT: OHINEWAI

LOGGED: R. B. W.

HOLE NO. 9783

DATE AUG '83

LENGTH 192.0 m

TRACKED M. F. S.

CORE BOXES: 51

ORIGINAL SCALE

1:100

SHEET 1 OF 7

DRG NO

INVESTIGATION GEOLOGY LTD consulting geologists		PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY FEATURE LOCATION CO-ORDINATES 337 239 5 E			HOLE No. 9783 632 339 9 N							
LOG OF DRILL HOLE		ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 6.4m										
DESCRIPTION OF CORE WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT		ROCK WEATHERING SW MW HW	RELATIVE STRENGTH S MS MW W	TEST RESULT 5 10 50	CORE LOSS/ LIFT % 5 10 50	DEPTH H.A.D. Core size casing m	GRAPHIC LOG SPACING OF NATURAL DEFECTS (cm) 50 10 5	DEFECT DESCRIPTION (JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.) SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc)	DATE/DEPTH ROD	WATER LEVEL Date	DRILL WATER LOSS % 0-100	WATER TEST RESULT
wk - very wk, dark red.-br. PEAT, laminated Drillers log: greywacke GRAVEL Very wk, grey-white SILT, pumiceous, laminated, carbonated streaks Very wk, gn.-white SILT, pumiceous wk - very wk, dk red.-br PEAT, lam. Very wk, br. gravelly, coarse SAND Very wk, brown, fine SAND with rare gravel slightly pumiceous Drillers log: 41.10 - 42.60 m Sands 42.60 - 49.70 m Gravel Drillers log: Blue silts Very wk, light greenish-bl to grey SILTY CLAY Very wk, br-gr. SILTY CLAY micaceous Very wk, grey to greenish-grey SILTY CLAY Very wk grey SILTY CLAY with rare fine sand, bedding horizontal Verywk, lt. br. SILTY fine SAND, carb. Very wk, dk red.-br. carb. SILTY SAND Very wk, lt brown SILTY fine SAND carb., coarser with depth Very wk, brown SILTY CLAY		15 11 16 12 13 17 14 18 15 19 20 17 18 21 19 22 20 20a	33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58	washdrilled 34.0 - 37.00 m Soft, non-plastic CORE NOT SEEN 37.4 - 38.8 m Soft, moist, plastic moist loose, wet, core disturbed loose, wet, moist CORE NOT SEEN 41.10 - 42.60 m washdrilled 42.60 - 49.70 m CORE NOT SEEN 49.70 - 50.60 m firm - stiff, moist, highly plastic stiff, moist, mod. plastic stiff, moist, highly plastic random, slickensided surfaces jt, 50° slickensided Very stiff, moist, highly plastic very stiff, moist, closely spaced slickensided surfaces dense, moist " " " " stiff, moist								
DRILLER: BROWN BROS STARTED: 5-8-83 FINISHED: 19-9-83 DRILL: FAILING		WEATHERING UW - Unweathered SW - Slightly weathered MW - Moderately weathered HW - Highly weathered CW - Completely weathered RELATIVE STRENGTH VS - Very Strong S - Strong MS - Moderately strong MW - Moderately weak W - Weak VW - Very weak		DEFECT LOG Spacing of natural defects Defects/ m of core		PROJECT: OHINEWAI HOLE NO: 9783 LENGTH 192.0 m CORE BOOKS 51 SHEET 2 OF 7		LOGGED R.B.W. DATE 1-9-83 FRACED M.F.S. CHECKED B.W.R. ORIGINAL SCALE 1:100 DRG NO				

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 6.4m

DESCRIPTION OF CORE WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc.), STRATIGRAPHIC UNIT	ROCK WEATHERING			TEST RESULT	CORE LOSS/ LIFT %	DEPTH H.A.D. Core size: casing m	GRAPHIC LOG	SPACING OF NATURAL DEFECTS (cms) 50 10 5 1	DEFECT DESCRIPTION (JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY — attitude, spacing, continuity, roughness, infilling, etc.) SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)	DATE/DEPTH ROD	WATER LEVEL	DRILL WATER LOSS %	WATER TEST RESULT
	SW	MW	HW										
Very wk, br. SILTY CLAY, carb				21		58	-X 00		firm, moist, highly plastic				
Very wk, gr-wh. SILTY fine SAND interbedded with wh. very fine SANDS (pumice)				22		59	X 00		Dense, moist				
Very wk, red.-br. SILTY CLAY, carb.				23					Very stiff, moist, highly plastic				
Mod. wk - wk dk red.-br. PEAT				24		60	-X -		moist				
Very wk, dk red.-br. SILTY CLAY carb.				25		61	-X -		stiff, moist, highly plastic				
Mod. wk, dk red.-br. PEAT				26		62	-X -		moist				
Very wk, dk gr SILTY CLAY, carb				27		63	-X -		Very stiff, highly plastic				
				27a			-X -						
				27		64	-X -						
Mod. wk - wk, dk br. PEAT bedded with v. wk greyish-br SILTY CLAY carb.				28		65	-X -		moist				
Very wk cream SILTY CLAY				28		66	-X -		firm, stiff, moist, highly plastic				
Very wk, lt br				29		67	-X -		stiff, moist, highly plastic, Jt. 60°, slickensided				
				29		68	-X -		Jt. 60°, slickensided				
Mod wk - wk, dk red.-br. PEAT				30		69	-X -		stiff, moist, highly plastic				
Very wk, lt red.-br. SILTY CLAY, carb				31		70	-X -		moist				
Mod. wk - wk dk red.-br. PEAT				32		71	-X -		stiff, moist, highly plastic				
Very wk, red.-br. SILTY CLAY, carb.				33		72	-X -		moist				
				34		73	-X -		Very stiff, moist, mod. plastic				
Mod. wk - wk, dk red.-br. PEAT lam.				35		74	-X -		highly carb				
Very wk lt grey SILTY SAND with rare fine gravel pumiceous				36		75	-X -		highly carb				
				37		76	-X -		compact, loose, wet				
Very wk, lt grey with blk coarse SAND wk, dk, red.-br. PEAT, laminated				38		77	-X -		loose				
Very wk, lt gr-br. SILTY CLAY				39		78	-X -		moist				
Very wk, dk br. SILTY CLAY, carb				40		79	-X -		Jt. 60°, slickensided				
Very wk, greenish-grey, fine SILTY CLAY with GRAVEL				41		80	-X -		Very stiff, moist - dry hly pl				
Very wk lt grey CLAY				42		81	-X -		very stiff, moist, hly pl.,				
				43		82	-X -		very stiff, moist, highly plastic				
				44		83	-X -		stiff, moist, highly plastic				
Very wk, lt grey SILTY SAND with rare gravel, pumiceous no apparent bedding				45		84	-X -		compact, moist				
				46		85	-X -						
				47		86	-X -						
				48		87	-X -						
				49		88	-X -						
				50		89	-X -						
Very wk, lt greyish green CLAY with rare sand, laminated				51		90	-X -		stiff, moist, highly plastic				
				52		91	-X -						
				53		92	-X -						
Very lt gr.-grn. CLAY with sand & fine gr.				54		93	-X -		stiff, moist, high plasticity				

DRILLER:

BROWN BROS

STARTED:

5 - 8 - 83

FINISHED:

19 - 9 - 83

DRILL:

FAILING

WEATHERING
 UW — Unweathered
 SW — Slightly weathered
 MW — Moderately weathered
 HW — Highly weathered
 CW — Completely weathered

RELATIVE STRENGTH
 VS — Very Strong
 S — Strong
 MS — Moderately strong
 MW — Moderately weak
 W — Weak
 VW — Very weak

DEFECT LOG

(cms)
 Spacing of
 natural
 defects.
 Defects/
 m of core

PROJECT: OHINEWAI

HOLE NO: 9783

LENGTH: 192.0m

CORE BOXES: 51

SHEET 3 OF 7

LOGGED: R. B. W.

DATE: SEPT '83

TRACED: M. F. S.

CHECKED: B. W. R.

ORIGINAL SCALE

1:100

DRG NO

INVESTIGATION GEOLOGY LTD consulting geologists		PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY FEATURE LOCATION CO-ORDINATES 337 239.5 E			HOLE No. 9783 632 339.9 N							
LOG OF DRILL HOLE		ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 6.4m										
DESCRIPTION OF CORE WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT	ROCK WEATHERING SW MW HW	RELATIVE STRENGTH MS MW W	TEST RESULT 5 10 50	CORE LOSS/ LIFT 5 10 50	DEPTH H.A.D. Core size, casing m	GRAPHIC LOG 50 10 5 (cm)	SPACING OF NATURAL DEFECTS 50 10 5 (cm)	DEFECT DESCRIPTION (JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.) SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)	DATE/DEPTH ROD	WATER LEVEL DATE	WATER LOSS % 0-100	WATER TEST RESULT
TAURANGA GROUP Very wk, lt greyish-green CLAY Very wk, lt brown CLAY, carb. Very wk, grey CLAY with horizon Wk, dk red.-br PEAT laminated Very wk, grey CLAY Very wk, dk br CLAY, carb. with peat laminations Very wk, grey CLAY Wk - very wk dk br CLAY, hly carb. Wk - very wk dk red.-br PEAT, lam. Very wk, gry-wh. SAND (fine, crs, gr, bedd. pumiceous) Mod wk - wk, dk red.-brn PEAT, lam. Very wk, dk br CLAY, highly carbonaceous Wk, dk, red.-br. PEAT Very wk, dk br. CLAY with gr. (pumice) carb. Very wk, lt grey SILTY fine SAND (pumice) Very wk, dk br CLAY carb Very wk, lt grey CLAY Very wk, lt grey SILTY SAND (pumice) Very wk, br. CLAY grading into v. wk lt gr clay, (carb.) Very wk, lt grey SILTY SAND with rare gravel pumiceous Very wk, lt brn CLAY, carb. with rare peat laminae Wk-very wk br. & lt greyish-grn CLAYST. laminated slightly carbonaceous Wk-very wk, lt greyish-grn CLAYSTONE laminated Wk, dk greyish-grn SILTY CLAYSTONE laminated S* GLEN AFTON CLAYSTONE Drillers log: indicates papa Wk, lt br. SILTY CLAYSTONE with rare v. fine sand Wk - v. wk dk grey SILTY CLAYST. laminated - S*								Stiff, moist, highly plastic. Jts, 10° slickensided lt, 50° slickensided moist Stiff, moist, high plasticity. Very stiff, moist, low plasticity. moist compact, moist moist Very stiff, moist, mod. plastic. moist stiff, moist, highly plastic. compact, moist Very stiff, moist, highly plastic. stiff, moist, highly plastic, highly compact, moist stiff, moist, highly plastic, highly compact, moist Jts - 45° slickensided compact, moist Very stiff, moist, highly plastic, small irregular fissures moist-dry, highly plastic. moist, highly plastic. Jts, 10-20° & 90° slickensided many small random fissures CORE NOT SEEN CORE highly disturbed Jts - 45° slickensided moist moist, dry CORE NOT SEEN (106.15 - 108.15 m)				
DRILLER: BROWN BROS STARTED: 5-8-83 FINISHED: 19-9-83 DRILL: FAILING		WEATHERING UW - Unweathered SW - Slightly weathered MW - Moderately weathered HW - Highly weathered CW - Completely weathered		RELATIVE STRENGTH VS - Very Strong S - Strong MS - Moderately strong MW - Moderately weak W - Weak VW - Very weak		DEFECT LOG Spacing of natural defects Defects/m of core		PROJECT OHINEWAI HOLE NO. 9783 LENGTH 192.0 m CORE BOXES 51 LOGGED R.B.W. DATE SEPT '83 TRACED M.F.S. CHECKED B.W.R. ORIGINAL SCALE 1:100				
EXPLANATION		SHEET 4 OF 7		DRG NO.								

INVESTIGATION GEOLOGY LTD

consulting geologists

PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY

HOLE
No.

9797

632 139. 12 N

FEATURE - LOCATION -

CO-ORDINATES 336 501. 67 E

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION - R.L. COLLAR 17.02 m

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT

ROCK WEATHERING
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

TEST RESULT
CORE LOSS/LIFT
%
5 10 50

DEPTH H.A.D.
Core size, casing
m
50 10 5 1

GRAPHIC LOG
SPACING OF NATURAL DEFECTS
(cm)
50 10 5 1

DEFECT DESCRIPTION

(JOINTS, BEDDING, SEAMS, SHAFTED, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)

SOIL DESCRIPTION

(consistency, relative density, water content, plasticity, grading, group symbol etc.)

DATE/DEPTH
R.Q.D.

WATER LEVEL
Date

DRILL WATER LOSS
%

0-100

WATER TEST RESULT

PUKEMIRO SANDSTONE

Wk - V wk, dk grn, fine-med, silty SANDSTONE with thin (< 100 mm) wk - v wk greyish-grn, fine sandy siltstone lenses, bedding subhoriz., highly glauconitic

Wk, greyish-grn, clayey SILTSTONE with thin (< 20 mm thick) wk, dk grn, silty, fine-med. sandstone laminae, highly glauconitic, bedding subhoriz., with rounded clasts of wk dk grn silty, fine-med SANDSTONE, highly glauconitic.
At 90.33 m a 92.70m 30mm thick irregularly shaped lens of wk yel.-brn CLAYSTONE, with bivalve fossils

80
81
82
83
84
85
86
87
88
89
90
91
92

Wash drilled to 86.96 m
see log from W. Leask,
STATE COAL MINES

Shear zones, subhoriz. 20mm thick, jts < 1mm apart, sm.

Jts 10-50 mm apart, sm.-silt
0-30°

11/1/85

14/1/85

DRILLER:
DRILLWELL

STARTED:
10-1-85


FINISHED:
17-1-85

DRILL:
TRIPLE-TUBE

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG



PROJECT: OHINEWAI

LOGGED: R. B. W.

HOLE NO: 9797

DATE: JAN '85

LENGTH: 36.33 m

TRACED: M. F. S.

CORE BOXES: 13

ORIGINAL SCALE

1:50

SHEET 1 OF 4

DRG NO

EXPLANATION

Casing at 86.96 m
Triple Tubed 87.0 m - 123.29 m

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 8.24m

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT

ROCK WEATHERING
SW
MW
HW

RELATIVE STRENGTH
VS
S
MS
MW
W
VW

TEST RESULT
CORE LOSS/LIFT
%

DEPTH
H.A.D.
Core size
Casing
m

GRAPHIC LOG
SPACING OF NATURAL DEFECTS
(cm)
0 10 20 30 40 50

DEFECT DESCRIPTION
(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)

SOIL DESCRIPTION
(consistency, relative density, water content, plasticity, grading, group symbol etc.)

DATE/DEPTH
R.O.D.

WATER LEVEL

DRILL WATER LOSS
%

WATER TEST RESULT

V.wk, dk.br. SILTY CLAY topsoil
V.wk, lt. orange-br. SILTY CLAY
V.wk, wh SILTY CLAY with minor sand
V.wk, dk br SILTY CLAY
V.wk, wh (red & br mottled) SILTY CLAY with some sand
V.wk, pink & wh mottled CLAYEY SAND
V.wk, wh SILTY CLAY with sand coarse sandy clay horizon
V.wk, wh CLAYEY CRS-F SAND with laminae of soft wh SILTY CLAY. Clayey sands are c.w pumice-ash - abrades to silt/clay/water mixture
V.wk, lt. yel-wh CLAYEY SANDS & soft SILTY CLAYS. c.w. pumice ash abrades to silt/clay/water. Minor rotten organic matter in basal 10cm
V.wk, dk.br. F PEAT
V.wk, dk.br. SILTY F SAND
V.wk, dk.br. SILTY CLAY with minor rotten leaf material
V.wk, lt grey-br SILTY v.f. SAND, with minor clay. Silt & clay proportions vary within unit
V.wk dk.br. - blk organic SILT & F PEAT
V.wk pale grey-br CLAYEY SILT
V.wk, dk br-grey v.f. SAND with minor SILT
100mm dk.br. org. silt, thin laminae alt. with v.f. sand
V.wk, lt & dk. br. lam. org. SILT
V.wk blk F. PEAT

TAURANGA GROUP

RELATIVE STRENGTH

VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

Spacing of natural defects.
Defects/m of core

PROJECT: OHINEWAI

HOLE NO: 9842

LENGTH: 191.85m

CORE BOXES: 65

LOGGED: B.G.S.

DATE: 7-29/5/85

TRACED: R.B.K.

CHECKED:

ORIGINAL SCALE

1:50

DRILLER:
DRILLWELL

STARTED:
7-5-85

FINISHED:
29-5-85

DRILL:
RIG NO.1

EXPLANATION

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 8.24m

DESCRIPTION OF CORE WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT	ROCK WEATHERING SW - Slightly weathered MW - Moderately weathered HW - Highly weathered CW - Completely weathered	RELATIVE STRENGTH VS - Very Strong S - Strong MS - Moderately strong MW - Moderately weak W - Weak VW - Very weak	TEST RESULT	CORE LOSS/LIFT %	DEPTH H.A.D. Core size casing m	GRAPHIC LOG	SPACING OF NATURAL DEFECTS (mm)	DEFECT DESCRIPTION (JOINTS, BEDDING, SEAMS, SHAFTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - altitude, spacing, continuity, roughness, infilling, etc.) SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)	DATE/DEPTH R.O.D.	WATER LEVEL Date	DRILL WATER LOSS %	WATER TEST RESULT
V. wk. blk f PEAT					13			Wet, stiff	7/5/85			
					14			Wet, soft				
								CORE LOSS 1.4m				
V. wk. blk f PEAT with wood frags					15			Wet				
V. wk. dk grey med-crs SAND with minor f. gravel. Org rich at base								CORE LOSS 0.10m Saturated, loose				
V. wk. blk PEAT with partly rotten wood, f. gravel at base								Saturated, disturbed sample				
								CORE LOSS 0.10m				
V. wk. lt br-grey f SAND, minor silt					16			Wet, compact (SP-sm)				
V. wk. blk f PEAT								Saturated, firm-stiff				
								CORE LOSS 0.75m				
V. wk. blk PEAT, wood frags dominant					17							
								CORE LOSS 0.30m				
as above												
V. wk. dk grey-br CLAYEY crs SILT					18			Compact				
V. wk. dk br-grey v.f. SAND with minor silt & rotten plant rootlets Basal 100mm org rich								Saturated compact (SP-sm)				
V. wk. lt br SILTY CLAY with basal 100mm f. PEAT horizon					19			Saturated, loose				
V. wk. dk grey f crs SAND (pumice)								CORE LOSS 0.70m				
V. wk. lt grey-br or dk grey SILTY CLAY with rare f. org material					20			Firm - stiff				
V. wk. lt grey br thinly bedded v.f. SAND, SILTY v.f. SAND & crs SAND, pumice tephra & tephra derived					21							
								CORE LOSS 0.50m				
V. wk. dk. br. med SAND with minor silt Tephra or tephra derived					22			Loose (SP-sm)				
V. wk. dk br med-crs SAND pumice. Sl coarsening - crs sand at base					23			Loose				
crs SAND (pumice) coarsening to f GRAVEL (pumice) at base								Loose				
								CORE LOSS 0.10m				
V. wk. lt grey-br crs SAND to f GRAVEL (pumice)					24							
V. wk. dk br-grey, med SAND with some silt Pumice Sl-med weath.					25			Saturated, loose				
								CORE LOSS 0.20m				

DRILLER:

DRILLWELL

STARTED:

7-5-85

FINISHED:

29-5-85

DRILL:

RIG No 1

WEATHERING

UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH

VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

Spacing of natural defects.
Defects/m of core

EXPLANATION

PROJECT: Ohinewai

HOLE NO: 9842

LENGTH: 191.85m

CORE BOXES: 65

LOGGED: B.G.S.

DATE: 7-29/5/85

TRACED: R.B.K.

CHECKED:

ORIGINAL SCALE

1:50

INVESTIGATION GEOLOGY LTD consulting geologists		PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY		HOLE No. 9842	
		FEATURE LOCATION		CO-ORDINATES 632 711 08 N 336 144 89 E	
LOG OF DRILL HOLE		ANGLE FROM HORIZONTAL 90°		DIRECTION R.L. COLLAR 8.24m	
DESCRIPTION OF CORE		ROCK WEATHERING		DEFECT DESCRIPTION	
WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT		RELATIVE STRENGTH		JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)	
TEST RESULT		CORE LOSS/ LIFT		SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)	
DEPTH H.A.D		GRAPHIC LOG		DATE/DEPTH	
SPACING OF NATURAL DEFECTS		WATER LEVEL		DRILL WATER LOSS	
WATER TEST RESULT		Date		0-100	
V. wk, dk br-grey med SAND with some silt. Pumice sl-mod weath		V. wk, blk F PEAT		CORE LOSS 0.20m	
V. wk, blk F PEAT		V. wk, blk F PEAT		Stiff	
V. wk, lt grey & dk br SANDY SILT		V. wk, blk F PEAT		Compact	
V. wk, lt grey-wh SILTY F SAND to F SANDY SILT, lam		V. wk, blk F PEAT		Compact	
V. wk, blk F PEAT with some partly decomposed wood		V. wk, blk F PEAT		CORE LOSS 0.10m	
V. wk, blk F PEAT		V. wk, blk F PEAT		Stiff	
V. wk, lt grey-br F GRAVEL, Fining down to crs SAND (pumice)		V. wk, blk F PEAT		Loose	
V. wk, lt grey-br F GRAVEL, Fining down to crs SAND (pumice)		V. wk, blk F PEAT		CORE LOSS 0.75m	
V. wk, lt grey-br F GRAVEL, Fining down to crs SAND (pumice)		V. wk, blk F PEAT		Loose	
V. wk, lt grey-br SILTY v.f. SAND		V. wk, blk F PEAT		Loose (sm)	
V. wk, dk br F SAND		V. wk, blk F PEAT		CORE LOSS 0.80m	
V. wk, dk br-grey F & crs SANDS		V. wk, blk F PEAT		Poorly graded (sp)	
V. wk, dk br org SILTY CLAY		V. wk, blk F PEAT		Loose, poorly graded sand	
V. wk, dk br F SAND		V. wk, blk F PEAT		crs well graded sand	
V. wk, lt grey med SAND, pumice		V. wk, blk F PEAT		Firm (CL)	
V. wk, dk br F SAND		V. wk, blk F PEAT		CORE LOSS 0.27m	
V. wk, lt grey med SAND, pumice		V. wk, blk F PEAT		Loose, poorly graded (sp)	
V. wk, dk grey-br org SILTY CLAY & F PEAT		V. wk, blk F PEAT		Loose (sp)	
V. wk, dk br grey SILTY CLAY with some F org frags		V. wk, blk F PEAT		Firm	
V. wk, lt grey-pinkish br SILTY CLAY		V. wk, blk F PEAT		V. stiff	
V. wk, blk org SILTY CLAY grading downwards into F PEAT		V. wk, blk F PEAT		CORE LOSS 0.10m	
V. wk, dk br to dk gm-grey SILTY CLAY with some decaying rootlets		V. wk, blk F PEAT		Stiff - v. stiff	
V. wk, dk gm-grey SILTY CLAY with some F sand. Micaceous F sand concentrated thin laminae. Sand content incr. downwards		V. wk, blk F PEAT		V. stiff	
V. wk, dk gm-grey SANDY CLAY micaceous, lam in part, all clayey F sand/silty clay		V. wk, blk F PEAT		V. stiff (CL)	
V. wk, dk grey CLAYEY F SAND Micaceous, massive		V. wk, blk F PEAT		V. stiff	
V. wk, dk grey CLAYEY F SAND Micaceous, massive		V. wk, blk F PEAT		Loose	
DRILLER: DRILLWELL		WEATHERING		PROJECT: Ohinewai	
STARTED: 7-3-85		RELATIVE STRENGTH		LOGGED: B.G.S.	
FINISHED: 29-5-85		EXPLANATION		HOLE NO: 9842	
DRILL: RIG No 1				LENGTH: 191.85m	
				CORE BOXES: 65	
				ORIGINAL SCALE 1:50	
				SHEET 3 OF 16	
				ORG NO	

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 8.24m

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT

ROCK WEATHERING
SW
MW
HW
CW

RELATIVE STRENGTH
VS
S
MS
MW
W
VW

TEST RESULT

CORE LOSS/LIFT
%
0-50

DEPTH H.A.D.
Core size casing
E

GRAPHIC LOG

SPACING OF NATURAL DEFECTS
(mm)
50 10 5 1

DEFECT DESCRIPTION
(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)
SOIL DESCRIPTION
(consistency, relative density, water content, plasticity, grading, group symbol etc.)

DATE/DEPTH
ROD

WATER LEVEL

DRILL WATER LOSS
%
0-100
Date

WATER TEST RESULT

V.wk. dk gm-grey to grey CLAYEY f SAND, micaceous

V.wk. dk grey SILTY CLAY to CLAYEY f SAND

decreasing sand content towards base

V.wk. dk gm-grey SILTY CLAY with some sand Thinly lam, micaceous. Variable proportion of sand, silt & clay

V.wk. dk grey, v f SAND with some clay. Massive micaceous fining towards base

gradational
V.wk. dk grey CLAYEY OR SILT with some sand
V.wk. dk grey SILTY CLAY with v rare sand in thin laminae

V.wk. dk grey SILTY CLAY with v rare sand (micaceous) homogenous

V.wk. dk grey SILTY CLAY with rare laminae of disintegrated leaf, thinly lam.

V.wk. f SAND

V.wk. dk grey - greyish br SILTY CLAY with v. rare rotten ? root frags

SW
MW
HW
CW

VS
S
MS
MW
W
VW

0-50

E

Compact

Stiff

Compact

Compact (Mu)

V. stiff

V. stiff

V. stiff

loose, poorly graded
CORE LOSS 0.10m
V. stiff

9/5/85

DRILLER:
DRILLWELL

STARTED:
7-5-85

FINISHED:
29-5-85

DRILL:
RIG No 1

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

Spacing of natural defects.
Defects/m of core

PROJECT: Ohinewai

HOLE NO: 9842

LENGTH: 191.85m

CORE BOXES: 65

SHEET 4 OF 10

DRG NO

LOGGED: B.G.S.

DATE: 7-29/5/85

TRACED: R.B.K.

CHECKED:

ORIGINAL SCALE

1:50

LOG OF DRILL HOLE

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR,
NAME, DEFECT TYPE, LITHOLOGICAL FEATURES
(bedding, foliation, mineralogy, cement etc),
STRATIGRAPHIC UNITROCK
WEATHERING
SW
MW
HWRELATIVE
STRENGTH
SS
MS
MW
W
VWTEST
RESULTCORE
LOSS/
LIFT
%DEPTH
H.A.D.
Core size
casing
m

GRAPHIC LOG

SPACING
OF
NATURAL
DEFECTSDEFECT DESCRIPTION
(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR
AND CRUSH ZONES, FOLIATION, SCHISTOSITY -
attitude, spacing, continuity, roughness, infilling,
etc.)SOIL DESCRIPTION
(consistency, relative density, water content,
plasticity, grading, group symbol etc.)

DATE/DEPTH

F.Q.D.

WATER
LEVELDRILL
WATER
LOSS
%WATER TEST
RESULT

V. wk, dk br-grey med SAND with
some silt. Pumice sl-med weath

V. wk, blk. F PEAT

V. wk, lt grey & dk br SANDY
SILT

V. wk, lt grey-wh SILTY F SAND
to F SANDY SILT, lam

V. wk, blk. F PEAT with some
partly decomposed wood

V. wk, lt grey-br F GRAVEL,
fining down to crs SAND
(pumice)

V. wk, lt grey F GRAVEL fining
down to med SAND pumice

V. wk, lt grey-br SILTY v. F. SAND

V. wk, dk br F SAND

V. wk, dk br-grey f & crs SANDS

V. wk, dk br org SILTY CLAY

V. wk, dk br F SAND

V. wk, lt grey med SAND, pumice

V. wk dk grey-br org SILTY CLAY
& F PEAT

V. wk, dk br grey SILTY CLAY with
some F org. frags

V. wk, lt grey-pinkish br
SILTY CLAY

V. wk, blk. org SILTY CLAY, grading
downwards into F PEAT

V. wk, dk br to dk gm-grey SILTY
CLAY with some decaying
rootlets.

V. wk, dk gm-grey SILTY CLAY
with some F sand. Micaceous
F sand concentrated thin laminae.
Sand content incr. downwards

V. wk, dk gm grey SANDY CLAY
micaceous, lam in part, alt
clayey f sand/silty clay

V. wk, dk grey CLAYEY F SAND
Micaceous, massive

TAURANGA GROUP

25
26
27
28
29
30
31
32
33
34
35
36
37

CORE LOSS 0.20m

Stiff

Compact

Compact

CORE LOSS 0.10m

Stiff

Loose

CORE LOSS 0.75m

Loose

Loose (SM)

CORE LOSS 0.80m

Poorly graded (SP)
Loose, F poorly graded sand
crs well graded sand
Firm (CL)

CORE LOSS 0.27m

Loose, poorly graded (SP)
Loose (SP)

Firm

V. stiff

CORE LOSS 0.10m

Stiff - v. stiff

V. stiff

V. stiff (CL)

V. stiff (CL)

V. stiff

Loose

8/5/85

9/5/85

DRILLER:
DRILLWELLSTARTED:
7-5-85FINISHED:
29-5-85DRILL:
RIG No 1

WEATHERING

UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH

VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

Spacing of
natural
defects.
Defects/
m of core

PROJECT: Ohinewai

LOGGED: B.G.S.

HOLE NO: 9842

DATE: 7-29/5/85

LENGTH: 191.85m

TRACED: R.B.K.

CORE BOXES: G5

CHECKED:

ORIGINAL SCALE

1:50

SHEET 3 OF 16

DRG NO

INVESTIGATION GEOLOGY LTD consulting geologists						PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY							HOLE No. 9842																						
						FEATURE LOCATION CO-ORDINATES 632 711.08 N 336 144.89 E																													
LOG OF DRILL HOLE						ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 8.24m																													
DESCRIPTION OF CORE						ROCK WEATHERING		RELATIVE STRENGTH		TEST RESULT		CORE LOSS/LIFT		DEPTH H.A.D.		GRAPHIC LOG		SPACING OF NATURAL DEFECTS		DEFECT DESCRIPTION		DATE/DEPTH		WATER LEVEL		DRILL WATER LOSS		WATER TEST RESULT							
WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, lamination, mineralogy, cement etc), STRATIGRAPHIC UNIT						SW MW HW		SS MS WS		%		Core size casing		E		(cm)		(consistency, relative density, water content, plasticity, grading, group symbol etc.)				Date		0-100											
V.wk. dk grn-grey to grey CLAYEY f SAND micaceous														38						Compact		9/5/85													
V.wk. dk grey SILTY CLAY to CLAYEY f SAND														39						Stiff															
decreasing sand content towards base														40																					
v.wk. dk grn-grey SILTY CLAY with some sand Thinly lam. micaceous. Variable proportion of sand, silt & clay														41						CORE LOSS 0.03m V. stiff															
v.wk. dk grey, v.f SAND with some clay Massive micaceous fining towards base														42						Compact															
gradational														43						Compact (ML)															
V.wk. dk grey CLAYEY OR SILT with some sand														44						V. stiff															
V.wk. dk grey SILTY CLAY with v rare sand in thin laminae														45																					
V.WK. dk grey SILTY CLAY with v rare sand (micaceous) homogenous														46						V. stiff															
V.WK. dk grey SILTY CLAY with rare laminae of disintegrated leaf, thinly lam.														47																					
V.WK. f SAND														48						V. stiff															
V.WK. dk grey - greyish br SILTY CLAY with v.rare rotten ? root frags														49						loose, poorly graded CORE LOSS 0.10m V. stiff															
TAURANGA GROUP														50																					
DRILLER:						WEATHERING						RELATIVE STRENGTH						DEFECT LOG						PROJECT: Ohinewai						LOGGED: B.G.S.					
DRILLWELL						UN -- Unweathered						VS -- Very Strong						Spacing of natural defects.						HOLE NO.: 9842						DATE: 7-29/5/85					
STARTED:						SW -- Slightly weathered						S -- Strong						Defects/m of core						LENGTH: 191.85m						TRACED: R.B.K.					
7-5-85						MW -- Moderately weathered						MS -- Moderately strong												CORE BOXES: G5						CHECKED:					
FINISHED:						HW -- Highly weathered						MW -- Moderately weak												ORIGINAL SCALE 1:50											
29-5-85						CW -- Completely weathered						W -- Weak												SHEET 4 OF 10						DRG NO.					
EXPLANATION						VW -- Very weak																													
DRILL: RIG No 1																																			

INVESTIGATION GEOLOGY LTD
consulting geologists

PROJECT OHINEWAI OPENCAST FEASIBILITY STUDY

HOLE No. **9842**

632 711 08 N
336 144 89 E

FEATURE LOCATION CO-ORDINATES

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL **90°** DIRECTION R.L. COLLAR **8.24m**

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT

ROCK WEATHERING
SW
MW
HW

RELATIVE STRENGTH
VS
S
MS
MW
W
VW

TEST RESULT

CORE LOSS/LIFT %

DEPTH H.A.D. m

GRAPHIC LOG

SPACING OF NATURAL DEFECTS (mm)

DEFECT DESCRIPTION

(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.)

SOIL DESCRIPTION

(consistency, relative density, water content, plasticity, grading, group symbol etc.)

DATE/DEPTH

R.O.D.

WATER LEVEL

DRILL WATER LOSS %

WATER TEST RESULT

TAURANGA GROUP

V. wk, dk br-grey med SAND with some silt. Pumice sl-mod weath

V. wk, blk. F PEAT

V. wk, lt grey & dk br SANDY SILT

V. wk, lt grey-wh SILTY F SAND to F SANDY SILT, lam

V. wk, blk. F PEAT with some partly decomposed wood

V. wk, lt grey-br F GRAVEL, fining down to crs SAND (pumice)

V. wk, lt grey F GRAVEL fining down to med SAND pumice

V. wk, lt grey-br SILTY v.F. SAND

V. wk, dk br F SAND

V. wk, dk br-grey F & crs SANDS

V. wk, dk br org SILTY CLAY

V. wk, dk br F SAND

V. wk, lt grey med SAND, pumice

V. wk dk grey-br org SILTY CLAY & F PEAT

V. wk, dk br grey SILTY CLAY with some F org. frags

V. wk, lt grey-pinkish br SILTY CLAY

V. wk, blk org SILTY CLAY, grading downwards into F PEAT


V. wk, dk br to dk gm-grey SILTY CLAY with some decaying rootlets.

V. wk, dk gm-grey SILTY CLAY with some F sand. Micaceous F sand concentrated thin laminae. Sand content incr downwards

V. wk, dk gm grey SANDY CLAY micaceous, lam in part, alt clayey F sand/silty clay

V. wk, dk grey CLAYEY F SAND micaceous, massive

25
26
27
28
29
30
31
32
33
34
35
36
37



CORE LOSS 0.20m

Stiff

Compact

Compact

CORE LOSS 0.10m

Stiff

Loose

CORE LOSS 0.75m

Loose

Loose (SM)

CORE LOSS 0.80m

Poorly graded (SP)

Loose, F poorly graded sand

crs well graded sand

Firm (CL)

CORE LOSS 0.27m

Loose, poorly graded (SP)

Loose (SP)

Firm

V. stiff

CORE LOSS 0.10m

Stiff - v. stiff

V. stiff

V. stiff (CL)

V. stiff

V. stiff (CL)

V. stiff

Loose

9/5/85

DRILLER:
DRILLWELL

STARTED:
7-5-85


FINISHED:
29-5-85

DRILL:
RIG No 1

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG



PROJECT: Ohinewai

HOLE NO: 9842

LENGTH: 191.85m

CORE BOXES: 65

SHEET 3 OF 16

LOGGED: B.G.S.

DATE: 7-29/5/85

TRACED: R.B.K.

CHECKED:

ORIGINAL SCALE

1:50

DRG NO

LOG OF DRILL HOLE

FEATURE LOCATION CO-ORDINATES
ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 8.24m

DESCRIPTION OF CORE	ROCK WEATHERING	RELATIVE STRENGTH	TEST RESULT	CORE LOSS/LIFT	DEPTH H.A.D.	GRAPHIC LOG	DEFECT DESCRIPTION	DATE/DEPTH	ROD	WATER LEVEL	DRILL WATER LOSS	WATER TEST RESULT
WEATHERING, RELATIVE STRENGTH, COLOUR, NAME, DEFECT TYPE, LITHOLOGICAL FEATURES (bedding, foliation, mineralogy, cement etc), STRATIGRAPHIC UNIT	SW MW HW CW	S MS MW W	S MS MW W	S MS MW W	Core size casing 5 10 15 20 25 30 35 40 45 50	SPACING OF NATURAL DEFECTS 50 10 5 1	(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR AND CRUSH ZONES, FOLIATION, SCHISTOSITY - attitude, spacing, continuity, roughness, infilling, etc.) SOIL DESCRIPTION (consistency, relative density, water content, plasticity, grading, group symbol etc.)					
V.Wk. dk grn-grey to grey CLAYEY F SAND, micaceous					38		Compact	9/5/85				
V.Wk. dk grey SILTY CLAY to CLAYEY F SAND					39		Stiff					
decreasing sand content towards base					40							
V.Wk. dk grn-grey SILTY CLAY with some sand. Thinly lam, micaceous. Variable proportion of sand, silt & clay					41		CORE LOSS 0.05m V. STIFF					
V.Wk. dk grey, v F SAND with some clay. Massive micaceous fining towards base					42		Compact					
gradational V.Wk. dk grey CLAYEY CRS SILT with some sand					43		Compact (M)					
V.Wk. dk grey SILTY CLAY with v rare sand in thin laminae					44		V. STIFF					
V.Wk. dk grey SILTY CLAY with v rare sand (micaceous) homogenous					45							
V.Wk. dk grey SILTY CLAY with rare laminae of disintegrated leaf, thinly lam.					46		V. STIFF					
V.Wk. dk grey SILTY CLAY with rare laminae of disintegrated leaf, thinly lam.					47		V. STIFF					
V.Wk. F SAND					48							
V.Wk. dk grey - greyish br SILTY CLAY with v. rare rotten ? root frags					49		loose, poorly graded CORE LOSS 0.10m V. STIFF					

DRILLER:
DRILLWELL

STARTED:

7-5-85

FINISHED:

29-5-85


DRILL:

RIG No 1

WEATHERING
UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH
VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG



EXPLANATION

PROJECT: Ohinewai

HOLE NO: 9842

LENGTH:

191.85m

CORE BOXES: 65

LOGGED: B.G.S.

DATE: 7-29/5/85

TRACED: R.B.K.

CHECKED:

ORIGINAL SCALE

1:50

LOG OF DRILL HOLE

ANGLE FROM HORIZONTAL 90° DIRECTION R.L. COLLAR 8.24

DESCRIPTION OF CORE

WEATHERING, RELATIVE STRENGTH, COLOUR,
NAME, DEFECT TYPE, LITHOLOGICAL FEATURES
(bedding, foliation, mineralogy, cement etc).
STRATIGRAPHIC UNITROCK
WEATHERING
SW
S
MS
MW
HW
CWRELATIVE
STRENGTH
S
MS
MW
HW
CW

TEST RESULT

CORE
LOSS/
LIFT
%DEPTH
H.A.D.
Core size
casing
m

GRAPHIC LOG

SPACING
OF
NATURAL
DEFECTS
(mm)

DEFECT DESCRIPTION

(JOINTS, BEDDING, SEAMS, SHATTER, SHEAR
AND CRUSH ZONES, FOLIATION, SCHISTOSITY -
attitude, spacing, continuity, roughness, infilling,
etc.)

SOIL DESCRIPTION

(consistency, relative density, water content,
plasticity, grading, group symbol etc.)

DATE/DEPTH

R.O.D.

WATER
LEVELDRILL
WATER
LOSS
%

0-100

WATER TEST
RESULT

V. rare CLAYEY F SAND, laminae

V. wk, dk br organic SILT

V. wk, dk br F SAND

V. wk, dk br F PEAT

V. wk, dk org br to lt grey SILTY
CLAYS with some F organic
materialV. wk, dk br organic SILT with
minor clay

v. wk, dk grey SILTY CLAY

greyish-br

V. wk, dk grey-br SILTY
CLAYV. wk, dk br F PEAT with some
rotten woodV. wk, dk grey-br SILTY CLAY with
some disintegrated leaf frags.V. wk, lt br -lt grey SILTY CLAY
with rare rotten F root
material. 40mm silty sand
layer at top. 50-80mm thk
organic rich horizons

V. wk, lt pinkish-brown SILTY CLAY

V. wk, dk br silty clay

V. wk, blk F PEAT & dk br
organic SILTY CLAY, with a
120mm v. wk. yel-br SILTY
SAND horizon50
51
52
53
54
55
56
57
58
59
60
61
62

v. stiff

Loose, poorly graded. (SP)
CORE LOSS 0.15m

Compact

v. stiff

Compact

v. stiff

v. stiff

CORE LOSS 3.0m

v. stiff
? cemented (sm)jts, random orient, slick, spacing
≤ 10mm, v. stiff

stiff

v. stiff

loose

9/5/85

DRILLER:
DRILLWELLSTARTED:
7-5-85FINISHED:
29-5-85DRILL:
RIG No 1

WEATHERING

UW - Unweathered
SW - Slightly weathered
MW - Moderately weathered
HW - Highly weathered
CW - Completely weathered

RELATIVE STRENGTH

VS - Very Strong
S - Strong
MS - Moderately strong
MW - Moderately weak
W - Weak
VW - Very weak

DEFECT LOG

(mm)
Spacing of
natural
defects.
Defects/
m of core

PROJECT: Ohinewai

LOGGED: B.G.S.

HOLE NO: 9842

DATE: 7-29/5/85

LENGTH: 191.85m

TRACED: R.B.K.

CORE BOXES: G5

CHECKED:

ORIGINAL SCALE

1:50